

DESCRIPTION:

PLANAR MONOLITHICS INDUSTRIES MODEL NUMBER LM-218-14-200W-SMF-HERM IS A HIGH POWER LIMITER THAT WORKS FROM 2 GHz TO 18 GHz THAT HANDLES 200 WATTS PEAK POWER WITH A PULSE WIDTH OF 1μSEC AND 0.1% DUTY CYCLE OR 2 WATTS CW. THIS MODEL IS HERMETICALLY SEALED.

SPECIFICATIONS:

- FREQUENCY:..... 2 TO 18 GHz
- INSERTION LOSS:..... 2.0 dB MAXIMUM @ Pin=-10dBm
- PEAK POWER:..... 200 WATTS MAXIMUM, 1μsec and 0.1% Duty Cycle
- AVERAGE POWER:..... 2 Watt CW MAXIMUM
- VSWR:..... 2.0:1 MAXIMUM
- LEAKAGE LEVEL:..... +15dBm MAXIMUM @ 2 Watt CW
- LOW LIMITING THRESHOLD: +6dBm TYPICAL
- RECOVERY TIME:..... 100nsec MAXIMUM @ Pin=27dBm
- CONNECTORS:..... SMA MALE / SMA FEMALE
- SIZE:..... 0.75 X 1.00 X .300 (H)
- WEIGHT:..... 1.5 OZ. TYPICAL
- SEALING:..... HERMETIC
- FINISH:..... GRAY EPOXY POLIMIDE COATING IAW MIL-C-22750, TYPE I OVER EPOXY POLIMIDE PRIMER IAW MIL-P-23377, TYPE I, CLASS 1 OR 3.

ENVIRONMENTAL RATINGS

- TEMPERATURE:..... -55°C TO +125°C (OPERATING) - NOTE 1
-65°C TO +125°C (STORAGE)
- THERMAL SHOCK..... MIL-STD-202F, METHOD 107D COND. A
- HUMIDITY:..... MIL-STD-202F, METHOD 103B COND. B
- SALT SPRAY:..... MIL-STD-202F, METHOD 101D+EST, COND. B
- VIBRATION:..... MIL-STD-202F, METHOD 204D COND. B
- SHOCK:..... MIL-STD-202F, METHOD 213B COND. C
- FUNGUS:..... MIL-STD-810F, METHOD 508.5


NOTE 1: Power Handling capability derated by 20% @ +125°C

DESIGNED TO MEET ALL ENVIRONMENTAL CONDITIONS. ACTUAL TESTING AVAILABLE FOR AN ADDITIONAL CHARGE.

NOTE: THE ABOVE SPECIFICATIONS ARE SUBJECT TO CHANGE OR REVISION

ALL DIMENSIONS ARE IN INCHES
TOLERANCES:
X.XX ±0.020
X.XXX ±0.010

REVISIONS				
ZONE	REV.	DESCRIPTION	DATE	APPROVED
	A1	ORIGINAL RELEASE	10/14/10	
	A2	ECN #14-0094	06/26/14	
	A3	ECN #24-0254	08/29/24	



M/N = MANUFACTURER PART NUMBER
O/N = OPTION NUMBER
S/N = SERIAL NUMBER

PMI CONFIDENTIAL AND PROPRIETARY

PART NO.		PLANAR MONOLITHICS INDUSTRIES FREDERICK, MARYLAND		
APPROVALS	DATE	TITLE PRODUCT FEATURE LM-218-14-200W-SMF-HERM HIGH POWER LIMITER		
DRAWN KM	8/12/10	SIZE A	FSCM NO. 05XQ0	DWG NO. 27013526
CHECKED				REV. A3
ISSUED				
		SCALE N:S	SHEET 1 of 1	