

## Frequency Tripler, Model U-3X

### Description:

Spacek Labs' passive frequency tripler, Model U-3X, has an input frequency range of 13.33 to 20 GHz generating an output frequency range of 40 to 60 GHz. This is a cost-effective frequency multiplier with similar models available from 18 to 110 GHz in complete waveguide output bandwidths from K-band to W-band. All designs are a balanced configuration to suppress undesired harmonics and are unconditionally stable for any input/output VSWR. To meet your needs, features can be added such as coaxial output adapters and additional filtering. MIL-spec or space-qualified units available.

### Features:


- Balanced Circuitry
- Unconditionally Stable
- Coaxial input, waveguide output, and filtering options available
- MIL-spec or space-qualified units available

### Electrical Specifications:

Description	Min.	Typ.	Max.
Input Frequency Range	13.33 GHz	-	20 GHz
Input Power Level	-	+15 dBm	-
Output Frequency Range	40 GHz	-	60 GHz
Conversion Loss	-	-	20.0 dB

### Mechanical Specifications:

Description	Specification
Connectors I/O	SMA(F) / WR-19
Dimensions OA	See outline
Material	Brass
Finish	Gold-plate
Weight	2.0 oz



**OUTLINE:** Dimensions in inches (Not to scale)

PASSIVE FREQUENCY MULTIPLIER