THIS DOCUMENT IS THE PROPERTY OF INTELLICONNECT. THE DESIGN AND SPECIFICA SHALL NOT BE REPRODUCED, COPIED NOR USED FOR MANUFACTURE OR SALE OF DE			<b>PART NO</b> 5154-P	1BK-000	-100P	
MATERIAL/FINISH PROPERTIES	MECHANICAL/ELECTRICA	MECHANICAL/ELECTRICAL PROPERTIES				
BODY: STAINLESS STEEL PER ASTM A582 OR EQUIVALENTCONNECTOR MEETCONTACT: BERYLLIUM COPPER PER ASTM B196 OR EQUIVALENTCONNECTOR DURAINSULATOR: PTFE PER ASTM D1710 OR EQUIVALENTMOUNTING: PER ESPLATING PROPERTIES:IMPEDANCE: 50 OFBODY: PASSIVATE PER QQ-P-35, TYPE IIFREQUENCY RANGCONTACT: .000030 MIN. GOLD PER MIL-G-45204 OVERVOLTAGE RATING:.000050 MIN. NICKEL PER QQ-N-290INSULATION RESIS		250 [6.4] IS NOMINAL : DC-22 GHz				
[5.33] Ø.210 2 PLCS O-RING (10.41) (1.27) .050 (1.27) .050 (0.50) (0.50) (0.210) (0.210) (1.27) .050 (0.210) (0.210) (1.27) .050 (0.210) (1.27) .050 (0.210) (1.27) .050 (0.210) (1.27) .050 (0.210) (1.27) .050 (0.210) (1.27) .050 (0.210) (1.27) .050 (0.210) (1.27) .050 (0.210) (1.27) .050 (0.210) (1.27) .050 (0.210) (1.27) .050 (0.210) (1.27) .050 (0.210) (1.27) .050 (0.210) (1.27) .050 (0.210) (1.27) .050 (0.210) (1.27) .050 (0.210) (0.210) (1.27) .050 (0.210) (0.21	DSS					
	IntelliConnect	TITLE: BMA STRAIGHT BULKHEAD MOUNT PLUG				
			MATERIAL & FINISH: PER TABLE ABOVE			
			CK BY: PCS : 11/07/08	APPR. BY DATE: 11/		
X.XXX DIM'S = INCHES	NS ARE REFERENCE * [X.XX] DIM'S = MILLIMETERS	CAGE CODE NO: 5N5S5	SCALE 6:1	SIZE A	REV A	
	NISH: 63 MICRO MAX. CONCENTRIC WITHIN .005 F.I.M.	SALES PART DRAWING 5154		•	SHEET	