



**SUMMARY TEST DATA
ON
P1T-200M18G-60-T-SFF**

PL18179/1549

Customer: _____ Tested By: K. Mansfield
SO No: _____ Temperature: +25°C
Model No: P1T-200M18G-60-T-SFF Date: 12/08/15
Serial No: PL18179/1549 Drawing No: 27622183 Rev: A1

TEST ITEM NO.	PARAMETERS	SPECIFIED VALUE	TEST RESULTS	QA/QC
1	Frequency Range:	0.5 – 18 GHz	0.5 – 18 GHz (See Plot)	
2	Insertion Loss:	1.0dB Typ, 2.5dB Max	2.2dB (See Plot)	
3	Isolation:	65dB Min	73dB (See Plot)	
4	VSWR: (J1 – “On” Only) (J2 – “On” or “Off”)	2.0:1 Max	Input 1.6:1 Output 1.8:1 See Plot	
5	Switching Speed:	25ns Max (50% TTL to 10/90% RF)	20ns See Typical Characteristics	
6	Operating Power:	+27dBm “Hot Switching” Max	Pass	
7	Control:	TTL Logic “0” = Off TTL Logic “1” = On	Pass	
8	DC Supply:	+15VDC @ 50 mA Max. -15VDC @ 75 mA Max.	10mA 19mA	

QA/QC Approval: _____ Date: _____



SUMMARY TEST DATA ON P1T-200M18G-60-T-SFF

PL18179/1549

(J1-J2) Insertion Loss and Return Loss



(J1 - J2) Isolation and Return Loss

