



**SUMMARY TEST DATA  
ON  
GMTA-1002**

Customer: \_\_\_\_\_ Tested By: JERRY WADE  
 SO No: \_\_\_\_\_ Temperature: +25°C  
 Model No: GMTA-1002 Date: 11/15/18  
 Serial No: PL23890/1846 Drawing No: 27619821 Rev: A4

TEST ITEM NO	PARAMETERS	SPECIFIED VALUE	TEST RESULTS	QA QC	
1	Frequency Range:	2 GHz to 18 GHz	2 GHz to 18 GHz	PMI QA 1	
2	Input Operating Range:	-18 to -23 dBm (2-18 GHz)	Pass		
3	Input VSWR:	2.5: 1 @ Pin = -10 dBm	2.35:1 See Plot		
4	Threshold Level:	Pin = -18 to -23 dBm @ 25°C	Max.= -19.4dBm Min.= -20.7 dBm		
5	Threshold Setting Stability:	±3.0 dB Max (Over Temp and Frequency)	±0.95dB		
6	Maximum Input Power:	+10 dBm (Without Damage)	Pass		
7	Detected Output:	TLL High (1) – On TLL Low (0) – Off	Pass		
8	Response Time:	100µs Max	Pass		
9	DC Supply:	+12VDC @ 50mA	+12VDC @ 37mA		PMI QA 1

4921 Robert J. Mathews Pkwy Suite 1, El Dorado Hills, CA 95762 USA Tel: (916) 542-1401 Fax: (916) 265-2597  
 Email: [sales@pmi-rf.com](mailto:sales@pmi-rf.com)



**SUMMARY TEST DATA  
ON  
GMTA-1002**

THRESHOLD SETTING STABILITY  
± 3 dB max OVER FREQUENCY @ TEMPERATURE

FREQ.	2 GHz	4 GHz	6 GHz	8 GHz	10 GHz	12 GHz	14 GHz	16 GHz	18 GHz
Pin @ 25 ° C	-20.2	-20.7	-20.4	-19.9	-19.7	-19.9	-19.7	-19.4	-20.1
Pin @ -20 ° C	-20.6	-20.8	-20.2	-19.9	-19.9	-20.1	-19.9	-20.1	-20.8
Pin @ 85 ° C	-20.0	-20.3	-19.3	-19.2	-19.5	-18.9	-19.0	-19.7	-20.4

QA/QC Approval:


PMI  
QA 1

Date:

11/20/8



**SUMMARY TEST DATA  
ON  
GMTA-1002**



4921 Robert J. Mathews Pkwy Suite 1, El Dorado Hills, CA 95762 USA Tel: (916) 542-1401 Fax: (916) 265-2597  
Email: [sales@pmi-rf.com](mailto:sales@pmi-rf.com)