



**SUMMARY TEST DATA
ON
PTP-2G18G-6G10G14G-CD-S4F**

Customer: _____ Tested By: J. Peacher
SO No: _____ Temperature: +25°C
Model No: PTP-2G18G-6G10G14G-CD-S4F Date: 12/6/18
Serial No: PL24003/1849 Drawing No: 27635220 Rev: A1

TEST. ITEM NO	PARAMETERS	SPECIFIED VALUE	TEST RESULTS	QA QC
1	FREQUENCY RANGE:	2.0 TO 18.0 GHz	2.0 TO 18.0 GHz	PMI QA 1
2	CROSSOVER FREQUENCY	6.0/10.0/14.0 GHz	Pass	
3	INSERTION LOSS:	1.5 dB MAXIMUM	Pass	
4	CROSSOVER RANGE:	±5% OF CROSSOVER	Pass	
5	REJECTION @ DC TO 1.7 GHz:	60 dB MINIMUM	Pass	
6	REJECTION ABOVE 21.0 GHz:	60 dB MINIMUM	Pass	
7	REJECTION @ ±15% OF CROSSOVER:	60 dB MINIMUM	Pass	
8	IN/OUT VSWR:	2.0:1 MAXIMUM	Pass	
9	PASSBAND RIPPLE:	0.5 dB MAXIMUM P-P	Pass	PMI QA 1
10	POWER HANDLING:	2 W CW MINIMUM	Pass	

QA/QC Approval: _____

PMI
QA 1

Date: _____

12/6/18

7311-F Grove Road, Frederick, MD 21704 USA
Phone: (301) 662-5019 Fax: (301) 662-1731
Email: sales@pmi-rf.com