



**SUMMARY TEST DATA
ON
LM-1G18G-15-3W-500WP-SFF**

Customer: _____
 SO No: _____
 Model No: LM-1G18G-15-3W-500WP-SFF
 Serial No: PL58835/2613

Tested By: Oliver K
 Temperature: +25°C
 Date: 3/26/2026
 Drawing No: 27634041 REV: A1

TEST ITEM NO.	PARAMETERS	SPECIFIED VALUE	Test Results	QA QC
1	Frequency Range:	1.0 to 18.0 GHz	1.0 to 18.0 GHz	PMI QA6
2	Insertion Loss:	2.5 dB Max. @ -20 dBm Input Power	2 dB See Graph	
3	Recovery Time:	100 ns Typical	Pass See Typical Characteristics	
4	VSWR:	2.0:1 Max. @ -20 dBm Input Power	1.76:1 In 1.73:1 Out See Graph	
5	RF Power Handling:	3 W CW Max.	Pass See Typical Characteristics	
		500W Peak Min. (1 μs PW, 0.1% DC)	Pass See Typical Characteristics	
6	Limiting Threshold:	+17 dBm Typ. (1 dB Compression)	+11 dBm See Graph	PMI QA6

QA/QC Approval: Anthony Kardly PMI QA6 Date: 4/7/26

7309-A Grove Road Frederick, MD 21704 USA Phone: (301) 662-5019 Fax: (301) 662-1731
 Email: sales@pmi-rf.com

**SUMMARY TEST DATA
ON
LM-1G18G-15-3W-500WP-SFF**

