




SUMMARY TEST DATA
ON
P2T-500M18G-80-T-515-SFF-4W-ST

Customer: _____
SO No: _____
Model No: P2T-500M18G-80-T-515-SFF-4W-ST
Serial No: PL61265/2630

Tested By: Adriana Martinez
Temperature: 25°C
Date: 7/31/2026
Drawing No: 27630243 Rev: B2

TEST ITEM NO.	PARAMETERS	SPECIFIED VALUE	TEST RESULTS	QA QC
1	Frequency Range	0.5 GHz to 18 GHz	0.5 GHz to 18 GHz	PMI QA8
2	Isolation	70 dB Min.	70.9 dB	
3	Insertion Loss	3.5 dB Typ.	2.73 dB	
4	VSWR: In/Out	2.0:1 Max.	1.66:1 In 1.58:1 Out	
5	Operating Power CW	4 Watts	Pass See Typical Characteristics	
6	Operating Power Peak	20 Watts, 50ns PW, 2Mhz PRF, 10% Duty	Pass See Typical Characteristics	
7	Switching Speed	60 ns Max.	Pass See Typical Characteristics	
8	Power Supply	5 V @ 150 mA -15 V @ 150 mA	5 V @ 61 mA -15 V @ 58 mA	
9	Control Signal	TTL LOGIC '1' : J1-J2 Low Loss '0' : J1-J3 Low Loss	Pass	PMI QA8

QA/QC Approval: 

Date: 8/4/26

7309-A Grove Road Frederick, MD 21704 USA Phone: (301)662-5019 Fax: (301)662-1731
Email: sales@quanticpmi.com

