



## Features and Benefits

Frequency range: 10MHz

Supply voltage: 2.5V

Current: 7mA Max.

Output waveform: Clipped Sine

Frequency stability vs. temperature:  $\pm 0.2$ PPM

Aging:  $\pm 1$ PPM per year

Phase noise: -152dBc/Hz@100KHz:

Operating temperature: -20°C to +70°C

Size: 5x3.2x1.7 mm

## Typical Applications

Portable Wireless Communications

Mobile Test Equipment

Radio


SATCOM System

## Description

TCXO5300BT-HS-10MHz\_CS-1312 is the high stability and low phase noise small size TCXO. It can be widely used in the portable communication devise.

## Mechanical Drawing & Pin Connections

Drawing No: MD150017-8



\*For control voltage version

**Specifications**

Oscillator Specification	Sym	Condition	Value			Unit	Note
			Min.	Typ.	Max.		
Operational Frequency	f <sub>0</sub>			10		MHz	
RF Output							
Output Waveform			Clipped sine				
Output Level			0.8			V <sub>p-p</sub>	
Output Load			10K//10pF				
Tri-state function		PIN#6 high or open	Pin#5 oscillation				
		PIN#6 low or GND	Pin#5 high impedance				
Power Supply							
Voltage	V <sub>cc</sub>	±5%		2.5		V	
Current					7	mA	
Frequency Control							
Control Voltage Range			0.5	1.5	2.5	V	
Tuning Range		Positive slope	±5			ppm	
EFC input impedance			100			Kohm	
Frequency Stability							
Tolerance		@+25°C			1.0	ppm	
Versus Temperature Reference to (FMAX+FMIN)/2					±0.2	ppm	
Versus Aging@+40°C		1 <sup>st</sup> year			±1.0	ppm	
G-sensitivity		Per axis			2.0	ppb/g	
Phase noise (typ.)		10 Hz		-83		dBc/Hz	For 40MHz
		100 Hz		-110			
		1 KHz		-135			
		10 KHz		-148			
		100 KHz		-152			
Environmental Conditions							
Operating temperature range		-20°C to +70°C					
Storage temperature range		-55°C to +110°C					
Reflow Profiles as per IPC/JEDEC J-STD-020C		≤260°C over 10 sec. Max.					

Note: Unless otherwise specified conditions are @+25°C