

NOTES:

- Removable "SMA" connectors.
 RF pin diameter = .02" x .07" in length.
 Input voltage pin is Ø.03".
- 4. Dimensions are in Inches/[mm.].
- 5. Ground Lug can be placed on input if requested

THIS DWG IS	PRELIMINARY	NOTE: THIS DWG IN		UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES	DRAWN	Judy Thomas	020104		^ ^	\ C * .		
UNLESS STAMPED		THIRD ANGLE PI	PROJECTION	TOLERANCES ARE: FRACTIONS DECIMALS ANGLES ±1/64 XX±.010 ±1/2*	CHECKED			JV 65 1 >-				
RELEASED	(⊕)—€	ENG.						microwave solutions inc.				
				XXX±.005 UNLESS OTHERWISE SPECIFIED 63 ALL OVER MATERIAL:	PROD.		NATIONAL	CITY	CALIFOR		ORNIA	
					QA		OUTLINE DRAWING, C-BAND, DROP-IN, AMPLIFIER					
					WALS			SIZE	FSCM NO.	DWG.NO		REV.
				FINISH:	OH (PPRO			A	65151	OL-0016	24-3	D
				DO NOT SCALE DRAWING	CAD FILE:	0L1624-3_D		WEIGHT:	SCA	LE: 2X 5	SHEET 1 (DF 1