



SUMMARY TEST DATA
ON
P1T-DC40G-65-T-292FF-1NS-OPT18G

Customer: _____
 SO No: _____
 Model No: P1T-DC40G-65-T-292FF-1NS-OPT18G
 Serial No: PL34836/2147

Tested By: J.ALEXIS
 Temperature: +25°C
 Date: 11/24/2021
 Drawing No: 27625063 Rev: A1

TEST ITEM NO	PARAMETERS	SPECIFIED VALUE	TEST RESULTS	QA QC	
1	Frequency Range:	DC to 18 GHz	DC to 18 GHz	PMI QA 2	
2	Insertion Loss:	4.5 dB Typ, 5.0 dB Max.	4.91 dB See Plot		
3	VSWR: In/Out	2.0:1 Typ. 2.2:1 Max.	In 1.96:1 Out 1.95 :1 See Plot		
4	Isolation:	60 dB Typ. 55 dB Min.	59 dB See Plot		
5	Switching Speed:	6 ns Typ. 7 ns Max.	6.6 ns See Typical Characteristics		
6	Rise/Fall Time:	1 ns Typ. 2 ns Max.	1.8 ns See Typical Characteristics		
7	Input Power:	+17 dBm CW Max.	Pass See Typical Characteristics		
8	Control Signal:	TTL "1" On	Pass		
9	Video Transients:	300 MHz BW (2-18 GHz): 85 mV P-P 20 MHz BW (2-18 GHz): 15 mV P-P	Pass See Typical Characteristics		
10	DC Supply:	+8 to +15V @ 15 mA Max. -8 to -15V @ 40 mA Max.	+15 V @ 4 mA -15 V @ 15 mA		PMI QA 2

QA/QC Approval: _____

PMI
QA 2

Date: 11/29/2021



**SUMMARY TEST DATA
ON
P1T-DC40G-65-T-292FF-1NS-OPT18G**

PL34836/2147

