


DESCRIPTION

PMI MODEL APD-2-218-M-BB-OPT1018 IS A 2 TO 18 GHz POWER DIVIDER OPTIMIZED FOR 10 TO 18 GHz, HAVING AN INSERTION LOSS OF 2.2 dB MAXIMUM BETWEEN 10 TO 18 GHz. THE SIZE IS 1.026" x 0.779" x 0.30".

SPECIFICATIONS

- FREQUENCY RANGE: 10 TO 18 GHz
- INSERTION LOSS: 2.2 dB MAXIMUM
- ISOLATION: 16 dB MINIMUM
- VSWR INPUT: 2.0:1 MAXIMUM
- VSWR OUTPUT: 1.8:1 MAXIMUM
- AMPLITUDE BALANCE: 0.2 dB MAXIMUM
- AVERAGE POWER HANDLING:
 - 0.3 WATTS WITH 100:1 VSWR
 - 1.5 WATTS WITH 2.0:1 VSWR
 - 2 WATTS WITH 1.2:1 VSWR
- SIZE: 0.779" (L) x 1.026" (W) x 0.300" (H)
- CONNECTORS: SMA - F



ENVIRONMENTAL RATINGS:

- TEMPERATURE: -55°C TO +85°C (OPERATING)
-65°C TO +125°C (STORAGE)
- HUMIDITY: MIL-STD-202F, METHOD 103B COND. B
- SHOCK: MIL-STD-202F, METHOD 213B COND. B
- VIBRATION: MIL-STD-202F, METHOD 204D COND. B
- ALTITUDE: MIL-STD-202F, METHOD 105C COND. B
- TEMPERATURE CYCLE: MIL-STD-202F, METHOD 107D COND. A

NOTE: SPECIFICATIONS WILL VARY OVER OPERATING TEMPERATURE
NOTE: THE ABOVE SPECIFICATIONS ARE SUBJECT TO CHANGE OR REVISION

ALL DIMENSIONS ARE IN INCHES
TOLERANCES:
X.XX ±0.020
X.XXX ±0.010

REVISIONS			
ZONE	REV.	DESCRIPTION	DATE
	-	PRELIMINARY	8/22/14

PLANAR MONOLITHICS INDUSTRIES, INC.

7311-F GROVE ROAD
FREDERICK, MARYLAND 21704 USA
TEL: 301-662-5019 FAX: 301-662-2029
WEBSITE: www.pmi-rf.com
E-MAIL: sales@pmi-rf.com



ISO 9001:2008 CERTIFIED

APPROVALS		DATE		TITLE	
DRAWN		8/22/14		PRODUCT FEATURE	
CHECKED				APD-2-218-M-BB-OPT1018	
ISSUED				10-18 GHz, POWER DIVIDER	
SIZE	FSCM NO.	DWG NO.	REV.		
A	05XQ0	PRELIMINARY	-		
SCALE N:S		SHEET		1 OF 1	