

SUMMARY TEST DATA ON PVVAN-4080-60-MP

Customer: _____ Tested By: G. Radtke
 Job No: _____ Temperature: +25° C
 Model No: PVVAN-4080-60-MP Date: 3/2/2021
 Serial No: 12987 Drawing No: 27622595 Rev: A1
 Part No: _____

TEST ITEM NO.	PARAMETERS	SPECIFIED VALUE	TEST RESULTS	QA QC	
1	Frequency Range:	4.0 GHz to 8.0 GHz	4.0 GHz to 8.0 GHz	PMI QA2	
2	Mean Attenuation Range:	60 dB	60.2 dB See Plot		
3	Insertion Loss:	2.5 dB Max.	2.2 dB See Plot		
4	VSWR:	2.0:1 Max	1.4:1 See Plot		
5	Power Rating:	+20 dBm (Operating) +30 dBm (Survival)	Pass		
6	Attenuation Flatness:	± 0.5 dB Typ. @ 10 dB ± 1.0 dB Typ. @ 20 dB ± 1.5 dB Typ. @ 40 dB ± 1.6 dB Typ. @ 60 dB	± 0.37 dB @ 10 dB ± 0.58 dB @ 20 dB ± 1.14 dB @ 40 dB ± 1.46 dB @ 60 dB See Plot		
7	Switching Time:	500 ns Max.	< 80 ns See Typical Characteristics		
8	Control:	10 dB / Volt Analog Controlled	Pass		
9	Power Supply:	+12 VDC @ 100 mA Typ. -12 VDC @ 50 mA Typ.	+12 VDC @ 30 mA -12 VDC @ 0 mA		PMI QA2

Voltage Control (V)	Programmed Attenuation (dB)	Attenuation (dB)	Accuracy of Attenuation (dB)	Flatness (± dB)
1	10	10.01	0.01	0.37
2	20	19.98	-0.02	0.58
3	30	30.01	0.01	0.93
4	40	40.08	0.08	1.14
5	50	50.08	0.08	1.25
6	60	60.15	0.15	1.46

QA/QC Approval:  **PMI QA2**

Date: 3/4/21

SUMMARY TEST DATA ON PVVAN-4080-60-MP

12987

