

SUMMARY TEST DATA ON DTA-0R5G18G-60-CD-1

Customer: _____
 SO No: _____
 Model No: DTA-0R5G18G-60-CD-1
 Serial No: 24027
 Part No: _____

Tested By: K. Mansfield
 Temperature: +25° C
 Date: 10/20/2022
 Drawing No: 27617783 Rev: A1

TEST ITEM NO.	PARAMETERS	SPECIFIED VALUE	TEST RESULTS	QA QC	
1	Frequency Range:	0.5 GHz – 18 GHz	0.5 GHz – 18 GHz	PMI QA2	
2	Insertion Loss:	4.5 dB Max.	4.4 dB See Plot		
3	VSWR:	2.0:1 Max.	1.8:1 See Plot		
4	Flatness to 20 dB:	± 1.0 dB Typ.	0.46 dB See Plot		
6	Flatness to 40 dB:	± 1.25 dB Typ.	0.52 dB See Plot		
7	Flatness to 60 dB:	± 3.0 dB Typ.	1.81 dB See Plot		
8	Accuracy of Attenuation 0 to 20 dB:	± 1.0 dB Typ.	0.22 dB See Plot		
9	Accuracy of Attenuation 20 to 40 dB:	± 1.5 dB Typ.	0.41 dB See Plot		
10	Accuracy of Attenuation 40 to 60 dB:	± 2.0 dB Typ.	0.62 dB See Plot		
11	Switching Speed:	1.0 us Max.	< 1.0 us See Typical Characteristics		
12	DC Supply:	+15VDC @ 150 mA Max.	114 mA		PMI QA2

Programed Attenuation	Attenuation	Accuracy of Attenuation	Flatness dB
dB	dB	dB	±dB
0.0625	0.07	-0.01	0.02
0.125	0.13	0.00	0.03
0.25	0.25	0.00	0.05
0.50	0.50	0.00	0.06
1.00	1.01	-0.01	0.07
2.00	2.02	-0.02	0.11
4.00	4.05	-0.05	0.19
8.00	8.10	-0.10	0.26
16.00	16.17	-0.34	0.41
32.00	32.34	-0.34	0.52
62.00	62.53	-0.53	2.00
63.94	64.63	-0.69	2.15

Programed Attenuation	Attenuation	Accuracy of Attenuation	Flatness dB
dB	dB	dB	±dB
5.00	5.04	-0.04	0.22
10.00	10.11	-0.11	0.27
15.00	15.09	-0.09	0.38
20.00	20.22	-0.22	0.46
25.00	25.23	-0.23	0.51
30.00	30.33	-0.33	0.51
35.00	35.34	-0.34	0.50
40.00	40.41	-0.41	0.51
45.00	45.34	-0.34	0.65
50.00	50.43	-0.43	0.88
55.00	55.46	-0.46	1.15
60.00	60.62	-0.62	1.81




QA/QC Approval:

PMI
QA2

Date: 10/21/2022

SUMMARY TEST DATA ON DTA-0R5G18G-60-CD-1

24027



**SUMMARY TEST DATA
ON
DTA-0R5G18G-60-CD-1**

24027

