

DESCRIPTION

PMI MODEL P1T-1G2G-85-R-SFF IS A REFLECTIVE, HIGH SPEED, SINGLE POLE SINGLE THROW SWITCH CAPABLE OF SWITCHING WITHIN 50 ns MAXIMUM. THE FREQUENCY RANGE IS 1.0 GHz TO 2.0 GHz. THIS SWITCH HAS > 80 dB ISOLATION.

SPECIFICATIONS

- FREQUENCY RANGE: 1.0 GHz TO 2.0 GHz
- IMPEDANCE: 50 Ω
- INPUT POWER: +30dBm MAX (SURVIVAL)
+20dBm MAX (OPERATING)
- INPUT VSWR: 1.5:1 TYP
- INSERTION LOSS: 0.75dB TYP
- ISOLATION: 80dB MIN
- SWITCHING SPEED: 50ns MAX
- DC VOLTAGE: +5VDC, 20mA TYP
-15VDC, 20mA TYP
- CONTROL: SOLDER PIN
TTL COMPATIBLE
"0" = INSERTION LOSS
"1" = ISOLATION
- CONNECTORS IN/OUT: SMA (F)
- SIZE: (L) 1.0" X (W) 1.0" X (H) 0.5"
- FINISH: BLUE EPOXY POLIMIDE COATING IAW MIL-C-22750, TYPE I OVER EPOXY POLIMIDE PRIMER IAW MIL-P-23377, TYPE I, CLASS 1 OR 3.

ENVIRONMENTAL RATINGS


- TEMPERATURE: -55°C TO + 85°C (OPERATING)
-65°C TO +125°C (STORAGE)
- HUMIDITY: MIL-STD-202F, METHOD 103B COND. B
- SHOCK: MIL-STD-202F, METHOD 213B COND. B
- VIBRATION: MIL-STD-202F, METHOD 204D COND. B
- ALTITUDE: MIL-STD-202F, METHOD 105C COND. B
- TEMPERATURE CYCLE: MIL-STD-202F, METHOD 107D COND. A

NOTE: SPECIFICATIONS WILL VARY OVER OPERATING TEMPERATURE
NOTE: THE ABOVE SPECIFICATIONS ARE SUBJECT TO CHANGE OR REVISION

ALL DIMENSIONS ARE IN INCHES
TOLERANCES:
X.XX ±0.020
X.XXX ±0.010

REVISIONS				
ZONE	REV.	DESCRIPTION	DATE	APPROVED
	1	ORIGINAL RELEASE	10/01/15	
	A1	ECN # 16-0108	8/24/16	

MECHANICAL OUTLINE



PMI CONFIDENTIAL AND PROPRIETARY

PLANAR MONOLITHICS INDUSTRIES, INC.

7311-F GROVE ROAD
FREDERICK, MARYLAND 21704 USA
TEL: 301-662-5019 FAX: 301-662-1731
WEBSITE: www.pmi-rf.com
E-MAIL: sales@pmi-rf.com
ISO 9001 CERTIFIED



APPROVALS		DATE	TITLE		
DRAWN: <i>B. Thomas</i>		10/01/15	PRODUCT FEATURE P1T-1G2G-85-R-SFF		
CHECKED			SIZE: A	FSCM NO.: 05XQ0	DWG NO.: 27027001
ISSUED					REV. A1
SCALE: N: S				SHEET 1 OF 1	