

DESCRIPTION

PMI MODEL P6T-0R5G18G-60-R-SFF IS A REFLECTIVE, SINGLE POLE, SIX THROW PIN DIODE SWITCH THAT OPERATES OVER THE 0.5 GHZ TO 18 GHZ FREQUENCY RANGE. THIS MODEL INCORPORATES A TTL COMPATIBLE DRIVER FOR EASY SYSTEM INTEGRATION.

SPECIFICATIONS

- FREQUENCY RANGE: 0.5 TO 18 GHZ
- ISOLATION: 60 dB MIN
- INSERTION LOSS: 3.5 dB MAX
- VSWR IN / OUT: 2.0 : 1 MAX
- INPUT POWER: +20 dBm CW MAX
- RF SWITCHING SPEED: 100nsec MAX
- DC VOLTAGE: +5 V @ 300 mA MAX
..... -5 V @ 100 mA MAX
- CONTROL SIGNAL: TTL LOGIC: "0"=ON, "1"=OFF
- CONNECTORS IN/OUT: SMA FEMALE
- CONTROL CONNECTORS: SOLDER PINS
- FINISH: GOLD PLATED


ENVIRONMENTAL RATINGS

- TEMPERATURE: -55°C TO +85°C (OPERATING)
..... -65°C TO +125°C (STORAGE)
- HUMIDITY: MIL-STD-202F, METHOD 103B COND. B
- SHOCK: MIL-STD-202F, METHOD 213B COND. B
- VIBRATION: MIL-STD-202F, METHOD 204D COND. B
- ALTITUDE: MIL-STD-202F, METHOD 105C COND. B
- TEMPERATURE CYCLE: MIL-STD-202F, METHOD 107

NOTE: SPECIFICATIONS WILL VARY OVER OPERATING TEMPERATURE
NOTE: THE ABOVE SPECIFICATIONS ARE SUBJECT TO CHANGE OR REVISION

REVISIONS				
ZONE	REV.	DESCRIPTION	DATE	APPROVED
	1	ORIGINAL RELEASE	6/9/17	
	A1	ECN # 17-0215	09/22/17	

MECHANICAL OUTLINE



PMI CONFIDENTIAL AND PROPRIETARY

PLANAR MONOLITHICS INDUSTRIES, INC.

7311-F GROVE ROAD
FREDERICK, MARYLAND 21704 USA
TEL: 301-662-5019 FAX: 301-662-1731
WEBSITE: www.pmi-rf.com
E-MAIL: sales@pmi-rf.com
ISO 9001 CERTIFIED



ALL DIMENSIONS ARE IN INCHES
TOLERANCES:
X.XX ±0.020
X.XXX ±0.010

APPROVALS		DATE	TITLE			
DRAWN <i>B. Thomas</i>		6/9/17	PRODUCT FEATURE P6T-0R5G18G-60-R-SFF			
CHECKED			SIZE A	FSCM NO. 05XQ0	DWG NO. 27031681	REV. A1
ISSUED			SCALE N: S	SHEET 1 OF 1		