

DESCRIPTION

PMI MODEL: P4T-100M18G-80-T-515-SFF-4W-IND IS A SINGLE POLE FOUR THROW ABSORPTIVE SWITCH. THIS MODEL HAS THE FOLLOWING SPECIFICATIONS.

SPECIFICATIONS

- FREQUENCY RANGE: 0.1 TO 18.0 GHz
- INSERTION LOSS: 4.5 dB TYP., 6.0 dB MAX
- ISOLATION: 80 dB MIN
- VSWR (ON/OFF): 2.0:1 MAX
- SWITCHING SPEED: 200ns MAX
- CONTROL LOGIC: INDIVIDUAL TTL CONTROL
"0" = LOW LOSS & "1" = ISOLATION
- OPERATING POWER: +36 dBm CW MAX
- DC SUPPLY: +5 & -15 VDC
- CONNECTORS IN/OUT: SMA (F) REMOVABLE
- CONTROL CONNECTORS: SOLDER PINS
- FINISH: EPOXY PAINTED BLUE

ENVIRONMENTAL RATINGS


- TEMPERATURE: -40°C TO + 85°C (OPERATING)
-55°C TO +125°C (STORAGE)
- HUMIDITY: MIL-STD-202G, METHOD 103B COND. B
- SHOCK: MIL-STD-202G, METHOD 213B COND. B
- VIBRATION: MIL-STD-202G, METHOD 204D COND. B
- ALTITUDE: MIL-STD-202G, METHOD 105C COND. B
- TEMPERATURE CYCLE: MIL-STD-202G, METHOD 107G COND. A

NOTE: SPECIFICATIONS WILL VARY OVER OPERATING TEMPERATURE
NOTE: THE ABOVE SPECIFICATIONS ARE SUBJECT TO CHANGE OR REVISION

ALL DIMENSIONS ARE IN INCHES
TOLERANCES:
X.XX ±0.020
X.XXX ±0.010

REVISIONS				
ZONE	REV.	DESCRIPTION	DATE	APPROVED
	A1	ORIGINAL RELEASE	04/19/17	

MECHANICAL OUTLINE



PMI CONFIDENTIAL AND PROPRIETARY

PLANAR MONOLITHICS INDUSTRIES, INC.

7311-F GROVE ROAD
FREDERICK, MARYLAND 21704 USA
TEL: 301-662-5019 FAX: 301-662-1731
WEBSITE: www.pmi-rf.com
E-MAIL: sales@pmi-rf.com
ISO 9001 CERTIFIED



APPROVALS		DATE	TITLE			
DRAWN		EMF	PRODUCT FEATURE			
REDRAW		JPU	P4T-100M18G-80-T-515-SFF-4W-IND			
ISSUED			SIZE	FSCM NO.	DWG NO.	REV.
			A	05XQ0	27032462	A1
			SCALE	N:S	SHEET	1 OF 1