


DESCRIPTION

THE PMI MODEL LM-10M14G-100W-1KWP-SFF-OPT17-ROHS IS AN RF LIMITER THAT WORKS IN THE RANGE OF FREQUENCIES FROM 10 MHz TO 7.0 GHz. THIS LIMITER CAN HANDLE 100 W CW OVER 1.0 TO 7.0 GHz, FOR ALL TEMPERATURES (-55 ° TO +85 ° C) AND 1 kW PEAK (10% WORK CYCLE, 10 us MAXIMUM PULSE WIDTH) ENERGY INPUT AND PROVIDES MAXIMUM LEAKAGE OF +17 dBm TYPICAL. THIS MODEL HAS A LOW LOSS OF INSERTION OF 1.5 dB MAX AND A RECOVERY TIME OF 100 ns MAX.

REVISIONS				
ZONE	REV.	DESCRIPTION	DATE	APPROVED
	A1	ORIGINAL RELEASE	03/14/23	
	B1	ECN # 25-0231	05/12/25	

SPECIFICATIONS

- FREQUENCY RANGE: 10 MHz TO 7.0 GHz
- INSERTION LOSS: 1.5 dB MAX
- INPUT/OUTPUT VSWR: 2.0 :1 MAXIMUM (AT -10dBm INPUT)
- IMPEDANCE: 50 OHMS
- INPUT POWER: 100 WATTS CW MAXIMUM (10 MHz – 7 GHz, TESTED 20 MHz– 7 GHz)
ALLTEMPERATURES (-55 °C TO +85 °C)
1 kW PEAK (1% DUTY CYCLE, 1 us PULSE WIDTH)
100 W PEAK (10% DUTY CYCLE, 10 us PULSE WIDTH)
- MAXIMUM FLAT LEAKAGE: 17 dBm TYPICAL AT 100W CW
- P1dB: 5 dBm MINIMUM
- RECOVERY TIME: 100 ns MAX
- FINISH: BLUE
- CONNECTORS: INPUT: SMA MALE
OUTPUT: SMA FEMALE



ENVIRONMENTAL RATINGS

IAW MIL-E-5400, CLASS 2 EQUIPMENT

- TEMPERATURE: ----- -55 °C TO +85 °C (OPERATING)
-62 °C TO +95 °C (STORAGE)
- VIBRATION: ----- 0.1 inchpp OR ± 10G, 5 ~ 500 Hz
(FIGURE 2, SHEET 1 OF 3, CURVE IV)
- SHOCK: ----- 15G, 11±1 ms
- HUMIDITY: ----- 100%
- ALTITUDE: ----- 70,000 Ft

NOTE: SPECIFICATIONS WILL VARY OVER OPERATING TEMPERATURE
NOTE: THE ABOVE SPECIFICATIONS ARE SUBJECT TO CHANGE OR REVISION

PMI CONFIDENTIAL AND PROPRIETARY

7309-A GROVE ROAD
FREDERICK, MARYLAND 21704 USA
TEL: (301)-662-5019, FAX: (301)-662-1731
WEB: www.pmi-rf.com, EMAIL: sales@pmi-rf.com
ISO 9001 CERTIFIED



APPROVALS		DATE	TITLE		
DRAWN <i>MDL</i>		03/14/23	OUTLINE		
REDAWN			LM-10M14G-100W-1KWP-SFF-OPT17-ROHS		
ISSUED			SIZE	FSCM NO.	DWG NO.
			A	05XQ0	27046120
			SCALE	N:S	SHEET 1 OF 1
					REV. B1