


DESCRIPTION:

PMI MODEL NUMBER SBA-100M18G-31D5-6B-SFF IS A SWITCHED BIT ATTENUATOR OPERATING FROM 0.1 TO 18 GHz DESIGNED TO BE SWITCHED BETWEEN A LOW LOSS STATE AND 31.5 dB IN 0.5 dB STEPS. THE SETTINGS ARE SELECTED BY 6 INDEPENDENT BIT CONTROLS.



ZONE	REV.	DESCRIPTION	DATE	APPROVED
	A1	ORIGINAL RELEASE	5/31/2023	
	A2	ECN #23-0182	9/28/23	

SPECIFICATIONS:

- FREQUENCY RANGE:..... 0.1 TO 18 GHz
- INSERTION LOSS:..... 6.0 dB MAX @ 25°C, 6.5 dB MAX OVER TEMP.
- ATTENUATION RANGE (OVER IL):..... 0 TO 31.5 dB
- STEP SIZE:..... 0.5 dB
- SWITCHING SPEED:..... 100 ns MAX
- VSWR (IN/OUT):..... 2.0:1 MAX
- MAX RF INPUT POWER:..... +20 dBm CW (OPERATING)
+27 dBm CW (SURVIVAL)
- DC VOLTAGE:..... +5 VDC ±5% @ 100 mA MAX
-5 VDC ±5% @ 100 mA MAX
- TTL CONTROL:..... 6 BITS
"1"=INSERTION LOSS"
"0"=ATTENUATION"
- RF CONNECTORS:..... SMA (F) REMOVABLE
- SIZE:..... 1.15" X 0.85" X 0.5"
- FINISH:..... PAINTED BLUE



BLOCK DIAGRAM



ENVIROMENTAL RATINGS:

- TEMPERATURE:..... -40°C TO +85°C (OPERATING)
-55°C TO +125°C (STORAGE)

NOTE: SPECIFICATIONS WILL VARY OVER TEMPERATURE
NOTE: THE ABOVE SPECIFICATIONS ARE SUBJECT TO CHANGE OR REVISION

PMI CONFIDENTIAL AND PROPRIETARY

UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES TOLERANCES ARE: FRACTIONS DECIMALS ANGLES ± .XX ± 0.02 ± .XXX ± 0.01		APPROVALS DATE DRAWN S AZHAR 5/31/2023 REDRAWN ISSUED		TITLE OUTLINE SBA-100M18G-31D5-6B-SFF	
		SIZE B FSCM NO. 05XQ0 DWG NO. 27046720	SCALE 3:1	REV. A2	SHEET 1 OF 1

Quantic PMI
PLANAR NONLINEAR

7309-A GROVE ROAD FREDERICK MARYLAND 21704 USA
 TEL: (301) 662-5019, FAX: (301) 662-1731
 WEB: WWW.QUANTICPMI.COM, EMAIL: SALES@QUANTICPMI.COM
 ISO 9001 CERTIFIED