ZONE	REV.	DESCRIPTION	DATE	APPROVED
	A1	ORIGINAL RELEASE	12/11/2023	

DESCRIPTION:

PLANAR MONOLITHICS INDUSTRIES MODEL NUMBER P1T-2G18G-60-R-55-SFF IS A SINGLE POLE REFLECTIVE SWITCH OPERATING OVER THE FREQUENCY RANGE OF 2.0 TO 18.0 GHz. IT HAS A MINIMUM ISOLATION OF 60 dB AND A MAXIMUM INSERTION LOSS OF 2 dB. THIS MODEL IS OUTFITTED WITH SMA FEMALE CONNECTORS.



SPECIFICATIONS:

- FREQUENCY RANGE:..... 2.0 TO 18.0 GHz
- INSERTION LOSS:..... 2.0 dB MAX
- ISOLATION:..... 60 dB MIN
- VSWR:..... 2.0:1 MAX
- SWITCHING SPEED:..... 25 ns MAX
- SUPPLY VOLTAGES :..... +5V @ 65 mA Max, -5V @ 65 mA MAX
- CONNECTORS:..... SMA FEMALE (FIELD REPLACABLE)
- FINISH:..... PAINTED BLUE
- INTERFACE:..... TTL (SEE TRUTH TABLE)

TRUTH TABLE	
L	OUTPUT
"1"	I.L.
"0"	ISO



ENVIRONMENTAL RATINGS:

- TEMPERATURE:..... -55°C TO +85°C (OPERATING)
  -60°C TO +125°C (STORAGE)
- HUMIDITY:..... MIL-STD-202, METHOD 103B COND. B
- MECHANICAL SHOCK:..... MIL-STD-202, METHOD 213B COND. B
- VIBRATION:..... MIL-STD-202, METHOD 204D COND. B
- ALTITUDE:..... MIL-STD-202, METHOD 105C COND. B
- TEMPERATURE CYCLE:..... MIL-STD-202, METHOD 105C COND. B

NOTE: SPECIFICATIONS WILL VARY OVER TEMPERATURE

NOTE: THE ABOVE SPECIFICATIONS ARE SUBJECT TO CHANGE OR REVISION

PMI CONFIDENTIAL AND PROPRIETARY

UNLESS OTHERWISE SPECIFIED
DIMENSIONS ARE IN INCHES
TOLERANCES ARE:
FRACTIONS ± DECIMALS .XX ± 0.02 .XXX ± 0.01 ANGLES ±

APPROVALS	DATE
DRAWN S AZHAR	12/11/2023
REDRAWN	
ISSUED	

Quantic PMI
PLANAR MONOLITHICS
7309-A GROVE ROAD FREDERICK MARYLAND 21704 USA
TEL: (301) 662-5019, FAX: (301) 662-1731
WEB: WWW.QUANTICPMI.COM, EMAIL: SALES@QUANTICPMI.COM
ISO 9001 CERTIFIED

TITLE: OUTLINE
P1T-2G18G-60-R-55-SFF

SIZE	FSCM NO.	DWG NO.	REV.
B	05XQ0	27047420	A1

SCALE 3:1 SHEET 1 OF 1