

DESCRIPTION:

PMI MODEL NO. ERDLVA-218-73-50MV-TK-1 IS A ERDLVA (EXTENDED RANGE DETECTOR LOG VIDEO AMPLIFIER). THIS UNIT OPERATES FROM 2.0 TO 18.0 GHZ. AND HAS A DYNAMIC RAGE OF 73 dB.

SPECIFICATIONS:

- FREQUENCY:..... 2.0 GHz TO 18.0 GHz
- FREQUENCY FLATNESS:..... ±2dB MAX
- VSWR:..... 2.5:1 MAX
- MAX INPUT LEVEL:..... +20dBm CW
- PULSE RESPONSE:..... PULSE (50ns – 100us)
- TSS:..... -72dBm MAX ROOM/ -70 dBm MAX HOT
- LOG DYNAMIC RANGE:..... -68dBm TO 5dBm
- LOG SLOPE:..... 50mV/dB ±5mV/dB INTO 100 OHMS LOAD
- LOG LINEARITY:..... ±1.5dB MAX
- RISE TIME:..... 25ns MAX
- RECOVERY TIME:..... 500ns MAX
- DC OFFSET:..... +150mV ±100mV
- POWER SUPPLY:..... +12VDC @ 330mA MAX, -12VDC @ 100mA MAX
- BASELINE SHIFT:.....100mV MAX
- FINISH:..... NICKEL PLATED

ENVIRONMENTAL RATINGS:


- TEMPERATURE:..... -30°C TO +85°C (OPERATING)
-30°C TO +100°C (STORAGE)
- HUMIDITY:..... MIL-STD-810F, METHOD 507.4
- SHOCK:..... MIL-STD-810F, METHOD 516.5
- VIBRATION:..... MIL-STD-810F, METHOD 514.5
- SALT & FOG:..... MIL-STD-810F, METHOD 509

NOTE: THE ABOVE SPECIFICATIONS ARE SUBJECT TO CHANGE OR REVISION

PMI CONFIDENTIAL AND PROPRIETARY

ALL DIMENSIONS ARE IN INCHES
TOLERANCES:
X.XX ±0.020
X.XXX ±0.010

REVISIONS				
ZONE	REV.	DESCRIPTION	DATE	APPROVED
	A1	ORIGINAL RELEASE	12/20/23	
	B1	ECN # 26-0150	7/30/26	



7309-A GROVE ROAD
FREDERICK, MARYLAND 21704 USA
TEL: (301)-662-5019, FAX: (301)-662-1731
WEB: www.quanticmpmi.com
EMAIL: sales@quanticmpmi.com
ISO 9001 CERTIFIED

Quantic PMI
PLANAR MONOLITHICS

APPROVALS		DATE		TITLE	
DRAWN S AZHAR		10/21/25		OUTLINE ERDLVA-218-73-50MV-TK-1	
REDRAWN				SIZE A	FSCM NO. 05XQ0
ISSUED				DWG NO. 27053460	REV. B1
				SCALE N:S	SHEET 1 OF 1