

**SUMMARY TEST DATA
ON
P3T-8G12G-70-T-SFF**

Customer: _____ SO No: _____ Tested By: K. Mansfield _____
 Model No: P3T-8G12G-70-T-SFF Temperature: 25°C
 Serial No: 34271 Date: 11/15/2023
 Part No: _____ Drawing No: 27026603 Rev: A1

TEST ITEM NO.	PARAMETERS	SPECIFIED VALUE	TEST RESULTS	QA QC
1	Frequency Range	8 GHz to 12 GHz	8 GHz to 12 GHz	PMI QA2
2	Impedance	50 Ω	Pass	✓
3	Operating Power CW	20 dBm Max	Pass See Typical Characteristics	
4	Survival Power CW	30 dBm Max	Pass See Typical Characteristics	
5	VSWR: In/Out	1.8 dB Typ.	1.22:1 In 1.58:1 Out	
6	Insertion Loss	2.8 dB Max.	2.2 dB	
7	Isolation	70 dB Min.	76.1 dB	
8	Switching Speed Max	100 ns Max.	Pass See Typical Characteristics	
9	Power Supply	5 V @ 150 mA Typ -15 V @ 100 mA Typ	5 V @ 73 mA -15 V @ 56 mA	✓
10	Control Signal	TTL LOGIC '0' : Insertion Loss '1' : Isolation	Pass	PMI QA2

QA/QC Approval:


PMI
QA2

Date:

11/16/2023

**SUMMARY TEST DATA
ON
P3T-8G12G-70-T-SFF**

34271



**SUMMARY TEST DATA
ON
P3T-8G12G-70-T-SFF**

34271

