



**SUMMARY TEST DATA
ON
TD-30T-SHS-218**

40014

Customer: _____ Tested By: Steve Baughman
SO No: _____ Temperature: +25°C
Model No: TD-30T-SHS-218 Date: 05/30/2014
Serial No: 140014 Drawing No: 27609530 Rev: A1
Part No: _____

TEST. ITEM NO	PARAMETERS	SPECIFIED VALUE	TEST RESULTS	QA QC
1	Frequency Range:	2 TO 18 GHz	2 TO 18 GHz	JE
2	VSWR:	3.0: 1 Max @ -20dBm	2.86 :1 (See Plot)	
3	Minimum Signal Level for Logic 1:	-20 dBm @ 2.0 GHz	-20.5 dBm @ 2.0 GHz	
		-17 dBm @ 18.0 GHz	-18.5 dBm @ 18.0 GHz	
4	Threshold Variation over Frequency (Any 1 GHz Window)	± 0.5 dB	0.4 ± dB	
5	Minimum Signal Level for Logic 0	-25 dBm	-21.5 dBm	
6	Dynamic Range:	+10 dBm Max	+10 dBm	
7	Propagation Delay from 50% of an input of -20 dBm	15 ns Max	See Typical Characteristics	
8	Propagation Delay from 50% of an input of +10 dBm	15 ns Max	See Typical Characteristics	
9	DC Supply:	+15VDC @ 100 mA Max	+15VDC @ 68.9 mA	↓
		-15VDC @ 100 mA Max	-15VDC @ 46.4 mA	

QA/QC Approval: _____

Date: _____

5/30/14



SUMMARY TEST DATA
ON
TD-30T-SHS-218

V000977052920140014

INPUT VSWR

CH2: B -M S +2.862 SWR
S.O dB/ REF .00 dB

