

**SUMMARY TEST DATA  
ON  
P1T-10M1G-80-T-SFF**

Customer: \_\_\_\_\_  
 SO No: \_\_\_\_\_  
 Model No: P1T-10M1G-80-T-SFF  
 Serial No: 54629

Tested By: K Craven  
 Temperature: 25°C  
 Date: 1/16/2026  
 Drawing No: 27626282 Rev: A1

TEST ITEM NO.	PARAMETERS	SPECIFIED VALUE	TEST RESULTS	QA QC	
1	Frequency Range	0.01 GHz to 1 GHz	0.01 GHz to 1 GHz	PMI QA2	
2	Impedance	50 Ω	Pass		
3	Input Power	+20 dBm Max Operating +30 dBm Max Survival	Pass See Typical Characteristics		
4	Input VSWR	1.5:1 Typ.	1.15:1 In		
5	Insertion Loss	1.3 dB Max.	1.03 dB		
6	Isolation	80 dB Typ.	83.4 dB		
7	Switching Speed	200 ns Max.	Pass See Typical Characteristics		
8	Power Supply	5 V @ 20 mA Typ -15 V @ 40 mA Typ	5 V @ 40 mA -15 V @ 70 mA		
9	Control Signal	TTL LOGIC '0' : Insertion Loss '1' : Isolation	Pass		PMI QA2




QA/QC Approval:  PMI  
QA2

Date: 2/10/2026

7309-A Grove Road Frederick, MD 21704 USA Phone: (301)662-5019 Fax: (301)662-1731  
 Email: sales@quanticpmi.com

SUMMARY TEST DATA  
ON  
P1T-10M1G-80-T-SFF


54629



7309-A Grove Road Frederick, MD 21704 USA Phone: (301)662-5019 Fax: (301)662-1731  
Email: sales@quanticpmi.com

SUMMARY TEST DATA  
ON  
P1T-10M1G-80-T-SFF

54629



7309-A Grove Road Frederick, MD 21704 USA Phone: (301)662-5019 Fax: (301)662-1731  
Email: sales@quanticpmi.com