

SUMMARY TEST DATA ON TD-30T-SHS-218-30DBAMP

Customer: _____
 SO No: _____
 Model No: TD-30T-SHS-218-30DBAMP
 Serial No: 64904
 Part No: _____

Tested By: JW
 Temperature: +25C
 Date: 2/26/2026
 Drawing No: 27610116 Rev: A1

TEST ITEM NO.	PARAMETERS	SPECIFIED VALUE	TEST RESULTS	QA QC
1	Frequency Range:	2 TO 18 GHz	2 TO 18 GHz	QA QC PM QA3
2	Minimum Signal Level for Threshold Detector to Respond	-45 dBm, ± 2.5 dBm	-46.25 to -44.25 dBm See Plot	
3	Propagation Delay: (from 50% of an input of -45 dBm)	10 ns Typ. 20 ns Max.	10 ns Typ. 20 ns Max.	
4	Propagation Delay: (from 50% RF Input to 50% Logic when Input to -20 dBm)	10 ns Typ. 20 ns Max.	10 ns Typ. 20 ns Max.	
5	DC Supply:	+12 VDC @ 250 mA Max. -12 VDC @ 120 mA Max.	+12 VDC @ 250 mA -12 VDC @ -65 mA	

QA/QC Approval: K. Klausner

Date: 2-26-26

1977022620264904

SUMMARY TEST DATA ON

