

**SUMMARY TEST DATA
ON
P3T-8G12G-70-T-SFF**

Customer: _____
 SO No: _____
 Model No: P3T-8G12G-70-T-SFF
 Serial No: 65013
 Part No: _____

Tested By: K. Mansfield/J. Fitzpatrick
 Temperature: +25°C
 Date: 5/5/2026
 Drawing No: 27626602 Rev: A1

TEST ITEM NO	PARAMETERS	SPECIFIED VALUE	TEST RESULTS	QA QC
1	Frequency Range:	8.0 TO 12.0 GHz	8.0 TO 12.0 GHz	PMI QA6
2	Insertion Loss:	2.8 dB Max.	2.45 dB See Plot	
3	Isolation:	70 dB Min.	71 dB See Plot	
4	VSWR: In/Out	1.8:1 Typ.	In 1.35:1 Out 1.83 :1 See Plot	
5	Switching Speed:	100 ns Max	<100 ns See Typical Characteristics	
6	Input Power:	+30 dBm Max. (Survival) +20 dBm Max. (Operating)	Pass See Typical Characteristics	
7	DC Supply:	+5 VDC @ 150 mA Typ. -15 VDC @ 100 mA Typ.	+5 VDC @ 78 mA -15 VDC @ 54 mA	
8	Control Signal:	LOGIC TABLE		
		E1 E2 E3	FUNCTION	
		0 1 1	J1-J2 "LOW LOSS"	
		1 0 1	J1-J3 "LOW LOSS"	
		1 1 0	J1-J4 "LOW LOSS"	PMI QA6

QA/QC Approval: Anthony Karoly PMI QA6

Date: 5/5/26

**SUMMARY TEST DATA
ON
P3T-8G12G-70-T-SFF**

65013

