SUMMARY TEST DATA
ON
P3T-8G12G-70-T-SFF

Customer: [redacted]
SO No: [redacted]
Model No: P3T-8G12G-70-T-SFF
Serial No: 65248
Part No: [redacted]


Tested By: A. Mousavi
Temperature: 25°C
Date: 10/12/2026
Drawing No: 27026602 **Rev:** A1


TEST ITEM NO.	PARAMETERS	SPECIFIED VALUE	TEST RESULTS	QA QC
1	Frequency Range	8 GHz to 12 GHz	**8 GHz to 12 GHz**	PMI QA6
2	Impedance	50 Ω	**Pass**	
3	Operating Power CW	20 dBm Max	**Pass See Typical Characteristics**	
4	Survival Power CW	30 dBm Max	**Pass See Typical Characteristics**	
5	VSWR: In/Out	1.8 dB Typ.	**1.28:1 In 1.5:1 Out**	
6	Insertion Loss	2.8 dB Max.	**2.33 dB**	
7	Isolation	70 dB Min.	**79.7 dB**	
8	Switching Speed Max	100 ns Max.	**Pass See Typical Characteristics**	
9	Power Supply	5 V @ 150 mA Typ -15 V @ 100 mA Typ	**5 V @ 80 mA** **-15 V @ 70 mA**	
10	Control Signal	TTL LOGIC '0' : Insertion Loss '1' : Isolation	**Pass**	PMI QA6

QA/QC Approval: Anthony Hardy PMI QA6 **Date:** 10/13/26

SUMMARY TEST DATA
ON
P3T-8G12G-70-T-SFF







SUMMARY TEST DATA
ON
P3T-8G12G-70-T-SFF

