


**DESCRIPTION:**

PMI MODEL NUMBER BPF-3D4G3D8G-10W-SFF IS A 3.4 TO 3.8 GHz BAND PASS FILTER. FEATURING 10 W POWER HANDLING, 1.5:1 VSWR, AND 1 dB INSERTION LOSS.

REVISIONS				
ZONE	REV.	DESCRIPTION	DATE	APPROVED
	-	PRELIMINARY	04/10/26	



**SPECIFICATIONS:**

- PASSBAND: 3.4 TO 3.8 GHz
- INSERTION LOSS: 1 dB MAX
- VSWR: 1.5:1 MAX
- REJECTION: 20 dB MIN @ DC TO 3.22 GHz & 3.88 TO 7 GHz
- INPUT POWER: 10 W CW MAX
- RF CONNECTORS: SMA FEMALE
- FINISH: PAINTED BLUE

**ENVIRONMENTAL RATINGS**

- TEMPERATURE: -40°C TO +70°C (OPERATING)  
-55°C TO +125°C (STORAGE)
- HUMIDITY: MIL-STD-202, METHOD 103B COND. B
- SHOCK: MIL-STD-202, METHOD 213B COND. B
- VIBRATION: MIL-STD-202, METHOD 204D COND. B
- ALTITUDE: MIL-STD-202, METHOD 105C COND. B
- TEMPERATURE CYCLE: MIL-STD-202, METHOD 107D COND. A

NOTE: SPECIFICATIONS WILL VARY OVER OPERATING TEMPERATURE  
NOTE: THE ABOVE SPECIFICATIONS ARE SUBJECT TO CHANGE OR REVISION

ALL DIMENSIONS ARE IN INCHES  
TOLERANCES:  
X.XX ±0.020  
X.XXX ±0.010  
WEIGHT: 2.75 oz.

**PMI CONFIDENTIAL AND PROPRIETARY**

**PLANAR MONOLITHICS INDUSTRIES, INC.**

7309-A GROVE ROAD  
FREDERICK, MARYLAND 21704 USA  
TEL: 301-662-5019 FAX: 301-662-1731  
WEBSITE: [www.pmi-rf.com](http://www.pmi-rf.com)  
E-MAIL: [sales@pmi-rf.com](mailto:sales@pmi-rf.com)  
ISO 9001 CERTIFIED



APPROVALS		DATE	TITLE		
DRAWN AG		04/10/26	PRODUCT FEATURE		
CHECKED			BPF-3D4G3D8G-10W-SFF		
ISSUED			SIZE	FSCM NO.	DWG NO.
			A	05XQ0	PRELIMINARY
			SCALE	N:S	SHEET 1 OF 1