

DESCRIPTION

PMI MODEL BPF-8G25R8G65R-SFF IS A BAND PASS FILTER WITH A CENTER FREQUENCY OF 8.45 GHz. IT HAS A MAX INSERTION LOSS OF 2.0 dB AND A MAXIMUM VSWR OF 1.5:1. THIS MODEL IS OUTFITTED WITH SMA FEMALE CONNECTORS.

SPECIFICATIONS

- PASSBAND FREQUENCY: ----- 8.25 TO 8.65 GHz
- INSERTION LOSS: ----- 2.0 dB MAXIMUM
- VSWR: ----- 1.5:1 MAXIMUM
- CENTER FREQUENCY: ----- 8.45 GHz
- REJECTION @ 7900 MHz: ----- 80 dB MINIMUM
- BANDWIDTH: ----- 400 MHz
- IMPEDANCE: ----- 50 OHMS
- INPUT/OUTPUT CONNECTOR: ----- SMA FEMALE

ENVIRONMENTAL RATINGS

- TEMPERATURE: ----- -45 °C TO +85 °C (OPERATING)
-55 °C TO +95 °C (STORAGE)
- HUMIDITY: ----- MIL-STD-202, METHOD 103B COND. B
- SHOCK: ----- MIL-STD-202, METHOD 213B COND. B
- VIBRATION: ----- MIL-STD-202, METHOD 204D COND. B
- ALTITUDE: ----- MIL-STD-202, METHOD 105C COND. B
- TEMPERATURE CYCLE: ----- MIL-STD-202, METHOD 107D COND. A

NOTE: SPECIFICATIONS WILL VARY OVER OPERATING TEMPERATURE


NOTE: THE ABOVE SPECIFICATIONS ARE SUBJECT TO CHANGE OR REVISION

PMI CONFIDENTIAL AND PROPRIETARY

ALL DIMENSIONS
ARE IN INCHES [mm]
TOLERANCES:
X.XX ±0.020
X.XXX ±0.010

REVISIONS				
ZONE	REV.	DESCRIPTION	DATE	APPROVED
	-	PRELIMINARY	4/19/2023	

MECHANICAL OUTLINE



PLANAR MONOLITHICS INDUSTRIES, INC.
7311-F GROVE ROAD
FREDERICK, MARYLAND 21704 USA
TEL: (301)-662-5019, FAX: (301)-662-1731
WEB: www.pmi-rf.com, EMAIL: sales@pmi-rf.com
ISO 9001 CERTIFIED



APPROVALS		DATE	TITLE			
DRAWN <i>AF</i>		4/19/23	PRODUCT FEATURE BPF-8G25R8G65R-SFF			
REDRAWN			SIZE	FSCM NO.	DWG NO.	REV.
ISSUED			A	05XQ0	PRELIMINARY	-
			SCALE	N:S	SHEET	1 OF 1