

DESCRIPTION

PMI MODEL: DD-2G4G-ZBS-SMF-ROHS IS A LOW NOISE TUNNEL DIODE DETECTOR OPERATING OVER THE 2 GHz TO 4 GHz FREQUENCY RANGE.

REVISIONS				
ZONE	REV.	DESCRIPTION	DATE	APPROVED
	-	PRELIMINARY	11/24/25	


SPECIFICATIONS

- FREQUENCY RANGE: ----- 2 GHz to 4 GHz
- SENSITIVITY: ----- 0.5 ± 0.05 mV/μW
- POLARITY: ----- NEGATIVE
- MAX INPUT POWER: ----- 100 mW
- VSWR: ----- 1.5:1 TYP, 2.0:1 MAX
- FLATNESS: ----- ±1.0 dB TYP
- CAPACITANCE: ----- 30 pf
- CONNECTORS IN/OUT: ----- SMA MALE/SMA FEMALE
- FINISH: ----- ALBALOY PLATED

LABEL



MECHANICAL OUTLINE



ENVIRONMENTAL RATINGS

- TEMPERATURE: ----- -54 °C TO +110 °C (OPERATING/STORAGE)
- HUMIDITY: ----- MIL-STD-202, METHOD 103B COND. B
- SHOCK: ----- MIL-STD-202, METHOD 213B COND. G (50g, 11 ms)
- VIBRATION: ----- MIL-STD-202, METHOD 204D COND. D (20 g, 10 - 2000 MHz)
- ALTITUDE: ----- MIL-STD-202, METHOD 105C COND. B
- TEMPERATURE CYCLE: ----- MIL-STD-202, METHOD 107D COND. A

ALL DIMENSIONS
ARE IN INCHES (mm)
TOLERANCES:
X,XX ±0.020
X,XXX ±0.010

NOTE: SPECIFICATIONS WILL VARY OVER OPERATING TEMPERATURE
NOTE: THE ABOVE SPECIFICATIONS ARE SUBJECT TO CHANGE OR REVISION

PMI CONFIDENTIAL AND PROPRIETARY

PLANAR MONOLITHICS INDUSTRIES, INC.

7309-A GROVE ROAD

FREDERICK, MARYLAND 21704 USA

TEL: (301)-662-5019, FAX: (301)-662-1731

WEB: www.pmi-rf.com, EMAIL: sales@pmi-rf.com

ISO 9001 CERTIFIED



APPROVALS		DATE	TITLE		
DRAWN	AG	11/24/25	PRODUCT FEATURE DD-2G4G-ZBS-SMF-ROHS		
REDRAWN			SIZE	FSCM NO.	DWG NO.
ISSUED			A	05XQ0	PRELIMINARY
			SCALE	N:S	SHEET 1 OF 1