

**SUMMARY TEST DATA  
ON  
HP-118-CD-SFF**

Customer: \_\_\_\_\_  
 SO No: Demo - PMI  
 Model No: HP-118-CD-SFF  
 Serial No: Demo - PMI

Tested By: Alfredo Lopez  
 Temperature: 25°C  
 Date: 8/23/2023  
 Drawing No: \_\_\_\_\_ REV: A1

TEST. ITEM NO	PARAMETERS	SPECIFIED VALUE	Test Results			QA QC
			+25°C	-40°C	+85°C	
1	Frequency Range:	1 to 18 GHz	1 to 18 GHz			
2	Passband Insertion Loss:	2.5 dB Max.	1.49 dB	1.88 dB	2.18 dB	
			See Graph			
3	Passband Input/Output VSWR:	2.0:1 Max.	1.6 :1	1.59 :1	1.72 :1	
			See Graph			
4	Rejection @ 350 MHz Rejection @ 500 MHz Rejection @ 600 MHz	60 dB Min. 40 dB Typ. 30 dB Typ.	-64.24 dB	-65.19 dB	-64.02 dB	
			-41.68 dB	-40.9 dB	-42.55 dB	
			-32.02 dB	-31.13 dB	-32.85 dB	
			See Graph			

QA/QC Approval: \_\_\_\_\_

Date: \_\_\_\_\_



# SUMMARY TEST DATA ON HP-118-CD-SFF

