



**TYPICAL PROPOSED
CHARACTERISTICS FOR
BROADBAND EQUALIZER
4-25 GHz**



DEC 7, 2020

PROPOSED BY:
PMI



**TYPICAL PROPOSED
CHARACTERISTICS FOR
BROADBAND EQUALIZER
4-25 GHz**

PROPOSED SPECIFICATIONS

ITEM NO.	PARAMETERS	SPECIFIED VALUE
1	Frequency	4 to 25 GHz
	Insertion loss	6.3 dB @ 4 GHz ± 0.5 dB
		2.3 dB @ 8 GHz ± 0.5 dB
2		2.5 dB @ 8 - 25 GHz
3	Input VSWR	1.7:1 Max
4	Output VSWR	1.7:1 Max
5	Slope	4 dB @ 4- 8 GHz ± 0.5 dB
7	Impedance	50 Ω .
8	Temperature	-40 to +85 deg C
9	Max Power	20 dBm CW Maximum
10	Input and Output	2.92mm Connector
11	Size	0.14" X0.47" X0.4"

Note: SIZE IS EXCLUDING CONNECTORS



**TYPICAL PROPOSED
CHARACTERISTICS FOR
BROADBAND EQUALIZER
4-25 GHz**

TYPICAL PERFORMANCE OF EQUALIZER

m1
freq=4.000GHz
dB(S(1,2))=-6.386

m2
freq=8.000GHz
dB(S(1,2))=-2.316

m3
freq=40.00GHz
dB(S(1,2))=-1.037

