

**FIRST ARTICLE  
TEST REPORT  
ON  
TWO  
SUCCESSIVE DETECTION LOG  
VIDEO AMPLIFIER (SDLVA)  
MODEL NUMBER SDLVA-0120-70**

**FOR  
PLANAR MONOLITHICS INDUSTRIES  
7311-G GROVE ROAD  
FREDERICK, MD 21701**

PREPARED BY *James Clark*  
ENVIRONMENTAL ENGINEERING

APPROVED BY *J. L. Hester*  
ENVIRONMENTAL MANAGER

Test Report Number C03622

**TABLE OF CONTENTS**

	<b>TEST SUMMARY PAGE</b>	<b>3</b>
<b>1.0</b>	<b>SUMMARY</b>	<b>4</b>
<b>1.1</b>	<b>Certification</b>	<b>4</b>
<b>1.2</b>	<b>Unit Under Test</b>	<b>4</b>
<b>1.3</b>	<b>Overall Test Results</b>	<b>4</b>
<b>2.0</b>	<b>GENERAL</b>	<b>4</b>
<b>2.1</b>	<b>Calibration</b>	<b>4</b>
<b>2.2</b>	<b>Standard Laboratory Ambient Test Conditions</b>	<b>5</b>
<b>2.3</b>	<b>Test Condition Tolerance</b>	<b>5</b>
<b>2.4</b>	<b>Test Fixture (Vibration and Shock</b>	<b>5</b>
<b>2.5</b>	<b>List of Environmental Test Equipment</b>	<b>6</b>
<b>3.0</b>	<b>APPLICABLE DOCUMENTS</b>	<b>6</b>
<b>4.0</b>	<b>TEST PROCEDURE</b>	<b>6</b>
<b>4.1</b>	<b>General</b>	<b>6</b>
<b>4.1.1</b>	<b>Purpose</b>	<b>7</b>
<b>4.2</b>	<b>First Article Test</b>	<b>7</b>
<b>4.2.1</b>	<b>General</b>	<b>7</b>
<b>4.2.2</b>	<b>Altitude</b>	<b>7</b>
<b>4.2.3</b>	<b>Vibration</b>	<b>7</b>
<b>4.2.4</b>	<b>Shock</b>	<b>8</b>
<b>4.2.5</b>	<b>Humidity</b>	<b>9</b>
<b>4.2.6</b>	<b>Overall Test Results</b>	<b>9</b>
<b>Table 1</b>	<b>VIBRATION PROFILE</b>	<b>9</b>
<b>Figure 1</b>	<b>Axis Definition</b>	<b>10</b>
<b>Appendix 1</b>	<b>Vibration Input Curves</b>	<b>11</b>
<b>Appendix 2</b>	<b>Shock Input Curves</b>	<b>15</b>

**Litton**

Amecom

**TEST SUMMARY PAGE**

**PURPOSE OF TEST:**

To determine the ability of the unit under test to withstand expected natural and dynamic stresses and to ensure that performance degradation or malfunctions will not be produced by the service environment.

**MANUFACTURER:**

Planar Monolithics Industries  
7311-G Grove Road  
Frederick, MD 21701

**MANUFACTURER'S TYPE OR MODEL NUMBER:**

Successive Detection Log Video Amplifier. Part Number SDLVA-0120-70

**DRAWINGS, SPECIFICATIONS OR EXHIBIT:**

Purchase Order Number 512520, Source Control Drawing Number 136079

**QUANTITY OF ITEMS TESTED:**

Two Units, S/N's SDL51022 and SDL51030

**SECURITY CLASSIFICATION OF TEST ITEMS:**

None Specified

**DATE TEST COMPLETED:**

01/06/96

**TEST CONDUCTED BY**

Litton/Amecom  
5115 Calvert Road  
College Park, MD 20740

**DISPOSITION OF SPECIMENS:**

Returned to Planar Monolithics Industries

**ABSTRACT:**

First Article testing was successfully completed on two Successive Detection Log Video Amplifiers. Environmental Testing consisted of Altitude, Vibration, Shock and Humidity. There was no structural damage or other anomalies as a result of the exposures. The assemblies were returned to Planar Monolithics Industries for further evaluation.

TEST REPORT NUMBER C03622

Page Number 3

## **1.0 SUMMARY**

### **1.1 Certification**

This test report certifies that the specimens identified in paragraph 1.2 were subjected to the First Article tests specified in Planar Monolithics Industries Purchase Order Number 512520.

### **1.2 Unit Under Test**

Two Successive Detection Log Video Amplifiers, P/N 40742-250F

### **1.3 Overall Test Results**

No anomalies were noted as a result of the environmental exposures.

## **2.0 GENERAL**

### **2.1 Calibration**

All test equipment was calibrated to standards that are traceable to the National Institute of Standards Technology (NIST). The test equipment had sufficient remaining calibration interval to complete the testing involved without re-calibration.

**2.2 Standard Laboratory Ambient Test Conditions**

The following conditions were used to establish normal performance characteristics under standard conditions:

Temperature:	25° +/- 5°C (77° +/- 9°F)
Relative Humidity:	80% or less
Barometric Pressure:	Local Prevailing

**2.3 Test Condition Tolerances**

The following control tolerances were used for test control:

**DYNAMICALLY INDUCED ENVIRONMENTS**

The vibration control system is equipped with over acceleration and loss of signal protection. Proper operation of these devices was demonstrated at 20% above the test tolerance and loss of signal 6 dB below the test tolerance subsequent to the start of testing.

Frequency	+/- 2% or +/- 2Hz (Whichever was greater)
Amplitude	+/- 10%
Time Duration	+/- 5%

**NATURAL ENVIRONMENTS**

Temperature	+/- 2° C
Humidity	+ 5% -0%
Altitude	+/- 5% (feet)

**2.4 Test Fixture (Vibration and Shock)**

The units under test were mounted to a cube which was in turn mounted to the vibration shaker head. The input control accelerometer was mounted on the test fixture as close as possible to the unit mounting point. Both units were mounted to the machine at the same time in different axes. At the completion of each axis the units were rotated 90° until each unit was exposed to shock and vibration in each of the three mutually perpendicular axes. No special fixturing was required for the Natural Environments.

**2.5 List of Environmental Test Equipment**

The following list of test equipment was utilized in the implementation of the tests described herein:

<u>Instrument</u>	<u>Manufacturer</u>	<u>Model No.</u>	<u>S/N</u>	<u>Cal Due date</u>
Vibration Exciter	Ling Elect.	A340	57	N/A
Vibration Amplifier	Ling Elect.	80728-72	218	N/A
Charge Amplifier System	Trig Tek	4114	240	08/31/95
Vibration Control System	Spectral Dynamics	1500	1047	12/02/95
Accelerometer	Endevco	2213E	PE69	05/22/96
Altitude Chamber	Conrad	F127705705	7277	11/10/96
Humidity Chamber	Thermotron	FM35CHM	219301	04/28/96

**3.0 APPLICABLE DOCUMENTS**

Purchase Order	- 512520
SCD 136079	- Test Procedure supplied by Planar Monolithics Ind.
MIL-STD-45662A	- Calibration System Requirements
MIL-STD-202F	- Test Methods for Electronic and Electrical Component Parts

**4.0 TEST PROCEDURE****4.1 General**

### **4.1.1 Purpose**

The First Article testing was conducted to determine if the units under test were constructed to withstand expected natural and dynamic stresses produced by the service environment.

## **4.2 First Article Tests**

### **4.2.1 General**

The First Article testing consisted of Altitude, Sinusoidal Vibration, Shock and Humidity in accordance with Source Control Drawing Number 136079, Paragraph 3.4.2 thru 3.4.5 and 4.3.1 and MIL-STD-202F

### **4.2.2 Altitude**

The Altitude test was performed in accordance with MIL-STD-202F, Method 105C, Condition B except that the maximum altitude was limited to 10,000 feet and the test items were non-operating.

The test assemblies were placed into the altitude chamber and the pressure was then reduced to 10,000 feet. The altitude was maintained at 10,000 feet for a period of 45 minutes, a sufficient time to allow all entrapped air in the chamber to escape. After the 45 minutes elapsed the chamber was again returned to sea level.

Upon completion of the altitude test the test assemblies were given to a representative of Planar Monolithics Ind. for electrical evaluation.

No anomalies were noted as a result of the altitude exposure.

### **4.2.3 Vibration**

The vibration test was performed in accordance with MIL-STD-202F, Method 204D, Test Condition B except the maximum "g" level attained was limited to 10 g peak.

The test items were mounted to the test fixture, identified in paragraph 2.4 of this report, and subjected to the test profile of Table 1 for a period of 240 minutes per axis. Each vibration sweep from 10Hz to 2000 Hz and return was traversed in 20 minutes. The test items were subjected to 12 such sweeps in each of the three axes.

**TABLE 1**

<u>Frequency</u> <u>Hz</u>	<u>Amplitude</u>
10 to 70	0.06" DA
70 to 2000	10 g

**Vibration Profile**

Upon completion of the vibration test in the first axis the test assemblies were rotated 90° and the test was repeated. The testing was repeated in each of the three mutually perpendicular axes for a total of 12 hours of vibration.

**4.2.4 Shock**

The Shock test was performed in accordance with MIL-STD-202F, Method 213B, Test Condition B except the maximum "g" level was limited to 30 g and the duration was extended to 11 milliseconds.

At the end of each vibration axis and prior to changing axes the shock test was performed. The test assemblies were subjected to 3 shocks in each direction of each axis in each of the three mutually perpendicular axes for a total of 18 shocks. Each shock was half sine, 30 g, 11 ms.

Upon completion of vibration and shock tests the test assemblies were given to a representative of Planar Monolithics Industries for electrical testing.

No anomalies were noted as a result of the vibration and shock tests.



#### **4.2.5 Humidity**

The Humidity test was performed in accordance with MIL-STD-202F, Method 103B, Test Condition B except 95% RH.



The test assemblies were placed into the humidity chamber and subjected to a 24 hour drying cycle at 40°C and a humidity of less than 50%. At the completion of the drying cycle the humidity was increased to 95% and 40°C. These conditions were maintained for a period of 96 hours.

Upon completion of the humidity test the test assemblies were given to a representative of Planar Monolithics Ind. for electrical evaluation.

No anomalies were noted as a result of the humidity exposure.

#### **4.2.6 Overall Test Results**

No anomalies were noted during or after any of the environmental test detailed in this test report.



**Figure 1**  
**AXIS DEFINITION**

**Litton**

Amecom

**Appendix 1**


**Vibration Input Curves**

AMERICAN MICROWAVE CORP.

20-Dec-95

13:38:06

100. SWEEP NUMBER 24



10.0 20.0 50.0 100.0 200.0 500.0 1K 2K  
S/N 22 X AXIS 30 Z AXIS LOG FREQ

UNIT # 1 TEST # 5

STORED RESPONSE CHANNEL 1

STORED RECORD 1


DURATION : 00:10:00

AMERICAN MICROWAVE CORP.

21-Dec-95  
19:24:35

100. SWEEP NUMBER 24

G



10.0 20.0 50.0 100.0 200.0 500.0 1K 2K  
S/N 22 Y AXIS 30 X AXIS LOG FREQ

UNIT # 1 TEST # 5

STORED RESPONSE CHANNEL 1

STORED RECORD 2


DURATION :

00:10:00

AMERICAN MICROWAVE CORP.

21-Dec-95  
23:48:07

SWEEP NUMBER 24



S/N 22 Z AXIS S/N 30 Y AXIS  
STORED RESPONSE CHANNEL 1  
STORED RECORD 3

DURATION :

00:10:00


**Appendix 2**

**Shock Input Curves**

810C PROCEDURE

S/N 22 X AXIS  
S/N 30 Z AXIS

21-Dec-95  
14:47:57



29.854

A C C E L E R A T I O N G

t, mSec 68.5

29.854

75.1 |  
DEFAULT TEST DEFINITION  
LAST RESPONSE WAVEFORM  
PEAK G 29.854

81.7 |

88.3 |  
UNIT # 1, TEST # 2  
3000 Hz RANGE  
PULSE DURATION 10.683


94.9 |

101.5



810C PROCEDURE  
S/N 22 X AXIS  
S/N 30 Z AXIS

21-Dec-95  
15:00:25



29.854

A C C E L E R A T I O N G

29.854

47.5

t, mSec

54.1 |  
DEFAULT TEST DEFINITION  
LAST RESPONSE WAVEFORM  
PEAK G 29.854

60.7 |

67.3 |

UNIT # 1, TEST # 2  
4000 HZ RANGE


73.9 |

80.5 |

PULSE DURATION 10.706

810C PROCEDURE  
S/N 22 Y AXIS  
S/N 30 X AXIS

21-Dec-95  
15:10:44



29.854

A C C E L E R A T I O N G

29.854

t, mSec 47.5

54.1 |  
DEFAULT TEST DEFINITION  
LAST RESPONSE WAVEFORM  
PEAK G 29.854

60.7 |


67.3 |  
UNIT # 1, TEST # 2  
4000 HZ RANGE

73.9 |  
PULSE DURATION 10.750

80.5 |

810C PROCEDURE  
S/N 22 Y AXIS  
S/O 30 X AXIS

21-Dec-95  
15:20:24



29.512

A C C E L E R A T I O N G

29.512

t, mSec 47.5


60.7 | 67.3 | 73.9 | 80.5

DEFAULT TEST DEFINITION  
LAST RESPONSE WAVEFORM  
PEAK G 29.512

UNIT # 1, TEST # 2  
4000 Hz RANGE  
PULSE DURATION 10.675

810C PROCEDURE  
S/N 22 Z AXIS  
S/N 30 Y AXIS

21-Dec-95  
23:54:19



29.512

A C C E L E R A T I O N G

29.512

t, mSec 47.5


54.1 | 60.7 | 67.3 | 73.9 | 80.5 |  
DEFAULT TEST DEFINITION  
LAST RESPONSE WAVEFORM  
PEAK G 29.512  
UNIT # 1, TEST # 2  
4000 Hz RANGE  
PULSE DURATION 10.744

810C PROCEDURE  
S/N 22 Z AXIS  
S/N 30 Y AXIS

21-Dec-95  
23:59:27

29.512

A C C E L E R A T I O N G



t, mSec 47.5

29.512

67.3 | 73.9 | 80.5  
UNIT # 1, TEST # 2  
4000 HZ RANGE  
PULSE DURATION 10.656

54.1 |  
DEFAULT TEST DEFINITION  
LAST RESPONSE WAVEFORM  
PEAK G 29.512

