

DESCRIPTION

THE MODEL P8T-10G31G-60-T-55-292FF IS A HIGH SPEED, SINGLE POLE, EIGHT THROW, ABSORPTIVE SWITCH CAPABLE OF SWITCHING WITHIN 50ns. THE FREQUENCY RANGE IS 10.0 TO 31.0 GHz AND THIS SWITCH HAS OVER 60dB OF ISOLATION.

SPECIFICATIONS

- FREQUENCY RANGE:..... 10.0 TO 31.0 GHz
- ISOLATION:..... 60dB MIN
- INSERTION LOSS:..... 8dB MAX
- VSWR IN/OUT:..... 2.0:1 MIN
- OPERATING INPUT POWER:..... +20dBm CW
- SWITCHING SPEED:..... 50 ns TYP.
- DC VOLTAGE AND CURRENT:..... +5VDC @ 100mA
 -5VDC @ 50mA
- CONTROL SIGNAL:..... EIGHT LINE TTL
 - E1 CONTROLS J1-J2
 - E2 CONTROLS J1-J3
 - E3 CONTROLS J1-J4
 - E4 CONTROLS J1-J5
 - E5 CONTROLS J1-J6
 - E6 CONTROLS J1-J7
 - E7 CONTROLS J1-J8
 - E8 CONTROLS J1-J9
- "0" ISOLATION
- "1" INSERTION LOSS
- CONNECTORS:..... 2.92mm (F) REMOVABLE
- FINISH:..... PAINTED BLUE

● SIZE:..... 4.0" X 1.5" X 0.4"


ENVIRONMENTAL RATINGS

- TEMPERATURE:..... -40°C TO +85°C (OPERATING)
 -55°C TO +125°C (STORAGE)

NOTE: SPECIFICATIONS WILL VARY OVER OPERATING TEMPERATURE
 NOTE: THE ABOVE SPECIFICATIONS ARE SUBJECT TO CHANGE OR REVISION

ALL DIMENSIONS ARE IN INCHES
 TOLERANCES:
 X.XX ±0.020
 X.XXX ±0.010
 WEIGHT: 2.75 oz.

REVISIONS				
ZONE	REV.	DESCRIPTION	DATE	APPROVED
	-	PRELIMINARY	11/11/22	



PMI CONFIDENTIAL AND PROPRIETARY

PLANAR MONOLITHICS INDUSTRIES, INC.

7311-F GROVE ROAD
 FREDERICK, MARYLAND 21704 USA
 TEL: 301-662-5019 FAX: 301-662-1731
 WEBSITE: www.pmi-rf.com
 E-MAIL: sales@pmi-rf.com
 ISO 9001 CERTIFIED



APPROVALS		DATE	TITLE			
DRAWN AF		11/11/22	PRODUCT FEATURE			
CHECKED			P8T-10G31G-60-T-55-292FF			
ISSUED			SIZE	FSCM NO.	DWG NO.	REV.
			A	05XQ0	PRELIMINARY	-
SCALE N:S			SHEET 1 OF 1			