


Capstick® Capacitor
Metallized Polymer Dielectric

CC

Stacked Metallized polymer capacitor
With -55 to +150C operating temperature range



- Surface-mount Capability
- Highest ripple current x capacitance density ratings in the industry
- Novel dielectric material: Ultra-low D.F, high operating temperature, self-healing properties
- Ultra-low ESR/ESL
- Lightweight <25% of equivalent MLCC
- Excellent for resonant circuits
- High dv/dt
- Efficient size
- Rugged construction
- Made in U.S.A

200 VDC / 140 VAC

PF Code	Value μ F	W Max	T Max	L Max	S	Typical ESR 500khz m Ω	Max Ripple current 85C 500khz (ARMS)	SRF[MHz]	Part Number
844	0.84	0.700 (17.8)	0.320 (8.1)	0.460 (11.7)	0.6	23	6.5	1.75	844K200CC6 _ _
185	1.8	0.700 (17.8)	0.320 (8.1)	0.880 (22.4)	0.6	13	12.6	1.4	185K200CC6 _ _

400 VDC / 280 VAC

424	0.42	0.700 (17.8)	0.320 (8.1)	0.460 (11.7)	0.6	23	6.5	3.6	424K400CC6 _ _
894	0.89	0.700 (17.8)	0.320 (8.1)	0.880 (22.4)	0.6	22	9.6	1.75	894K400CC6 _ _

Dimensions in inches, metric (mm) in parenthesis
Tolerance: K ($\pm 10\%$) standard, J ($\pm 5\%$) available
RoHS part number information

No suffix indicates RoHS-5 compliant standard part number. RoHS-5 product does not contain five of the RoHS banned materials (Hg, CrVI, Cd, PBB and PBDE) in levels exceeding the industry defined limits. Component lead wires are plated with Sn / Pb and match conventional SnPb 1 assembly requirements

For a RoHS-6 compliant part, add a -FA suffix. RoHS-6 product does not contain any of the six RoHS banned materials (Hg, CrVI, Cd, PBB, PBDE and Pb) in levels exceeding

"(optional) add "G" for SMD version, for example 844K200CC6G"

"(optional) add "-FA" for Pb-Free version, for example 844K200CC6-FA"

Note: Standard part has Sn/Pb plated terminations and does not meet latest RoHS requirements, for RoHS compliant version, add "-FA" suffix"


Electrical	Performance	Physical
Capacitance Range: 0.42 μF to 1.8 μF @ 1KHz Tolerance: Available in $\pm 5\%$, 10% [standard], 20% Voltage Range: 200, 400, VDC Dissipation Factor: $\leq 0.1\%$ @ 25°C, 1KHz Insulation Resistance: 1000F or 100GΩ, whichever is less at rated voltage and 25C Dielectric Strength: 1.3 x RVDC, 2 seconds max. Self Inductance: 2 to 6nh typical Temperature Range: -55°C to 150°C operating -55°C to 105°C @ rated DC voltage derate voltage 1.66% / °C above 105°C max operating temperature; 150C	Accelerated DC Voltage Life Test: 1,000 Hours, 85°C, 1.25 x Rated VDC Δ C/C $\leq 5\%$ DF $\leq 1.0\%$, 1KHz, 25°C IR $\geq 1,000$ Megohm x μF Need not exceed 1,000 Megohms Moisture Test: 85°C / 85% RH / 21 days Applied Voltage: zero bias Δ C/C $\leq 7\%$ DF $\leq 0.1\%$, 1KHz, 25°C IR $\geq 30\%$ of initial limit Long Term Stability: After 2 years storage, standard environment Δ C/C $\leq 2\%$	Vibration: Mil Std 202 Method 204D Solder Resistance: Thru-hole wave: 260°C, 5 Sec. Δ C/C $\leq 2\%$ SMD reflow: 220°C, 30 Sec. Δ C/C 2% Construction: Non-inductively constructed with metallized polymer dielectric. Parallel plate-multilayer polymer (MLPI) design. Electrode: Aluminum metallization Case: UL94V-0 rated epoxy coating Lead-Frame Material: Tinned Cu Alloy Lead-Frame Lead Spacing: .600" (15.0mm) nominal Marking: +PF+ type capacitance code, tolerance code, Anti-static tube. SMD units dry packed with desiccant

Capstick® Capacitor
Metallized Polymer Dielectric


CC

Electrical Characteristics


Impedance Vs Frequency




ESR Vs Frequency



Ripple Current Limit Vs Frequency -55 to +85C












Maximum RMS Voltage Vs Frequency



Capstick® Capacitor
Metallized Polymer Dielectric

CC

Electrical Characteristics 200V and 400V Ratings



Evans **Trusted Brands. Single Source.**
GROUP **Hi-Rel Capacitors for Mission Critical Systems.**

Uniting four industry leaders—Evans, Paktron, UTC, and Eulex—Evans Group delivers the industry's most specialized and comprehensive capacitor portfolio. Together, we provide power-dense, high-reliability solutions engineered for mission-critical environments across defense, aerospace, energy, and advanced RF systems.

Paktron
1205 McConville Road Lynchburg, VA 24504

T +1 434.239.6941
E paktron@evans-group.com
URL www.evans-group.com/paktron