

SUMMARY TEST DATA ON PS-90-2040

Customer: _____
 Job No: _____
 Model No: PS-90-2040
 Serial No: PL02602

Tested By: E. KRETZ
 Date: 01/24/2020
 Temp: 25°C
 Drawing No: 27615688 Rev: A1

TEST ITEM NO.	PARAMETERS	SPECIFIED VALUE	TEST RESULTS	QA QC	
1	Frequency Range:	2.0 GHz to 4.0 GHz	2.0 GHz to 4.0 GHz	PMI QA 1	
2	Insertion Loss:	2.5 dB Typ. 3.0 dB Max.	1.2 dB See Plot		
3	VSWR Input:	2.0:1 Typ. 2.5:1 Max.	1.5:1 See Plot		
4	Operating Input Power:	+20 dBm Operating	+20 dBm See Typical Characteristics		
5	Speed:	75 ns MAXIMUM On/Off	< 75 ns See Typical Characteristics		
6	Maximum RF Input:	0.5 Watt CW, 1 µsec Pulse Width Survival	0.5 Watt CW, 1 µsec See Typical Characteristics		
7	Carrier Suppression:	20 dB Typical	<20 dB See Typical Characteristics		
8	DC Supply:	+5 VDC @ 75 mA Max. -5 VDC @ 20 mA Max.	+5 VDC @ 36 mA -5 VDC @ 5 mA		PMI QA 1

QA/QC Approval:  PMI
QA 1

Date: 1/27/20

SUMMARY TEST DATA ON PS-90-2040

