

**SUMMARY TEST DATA
ON
APD-2-800M2D5G-NFF-50W**

Customer: _____ Tested By: M. Hanken
 SO No: _____ Temperature: +25°C
 Model No: APD-2-800M2D5G-NFF-50W Date: 08/24/2020
 Serial No: PL02812 Drawing No: 27627902 Rev: A1
 Part No: _____

TEST ITEM NO	PARAMETERS	SPECIFIED VALUE	TEST RESULTS	QA QC
1	Frequency Range	0.8 TO 2.5 GHz	0.8 TO 2.5 GHz	PMI QA 2
2	Insertion Loss	≤0.4 dB	0.39 dB (See Plot)	
3	VSWR	≤1.25:1	1.14:1 (INPUT) 1.15:1 (OUTPUT) (See Plot)	
4	Isolation	22 dB Minimum	25 dB (See Plot)	
5	Amplitude Balance	≤±0.2 dB	≤± 0.1 dB (See Plot)	
6	Phase Balance	≤±2°	≤± 2° See Typical Characteristics	
7	Power Handling	Forward ≤50 W Reversed ≤1 W	Pass	
8	Impedance	50 Ω	50 Ω	



QA/QC Approval:  PMI QA 2 Date: 8.25.2020

**SUMMARY TEST DATA
ON
APD-2-800M2D5G-NFF-50W**

Insertion Loss, VSWR

J2

J3



Isolation

Amplitude Balance

