

Planar Monolithics Industries  
 7311 F Grove Road, Frederick MD 21704 USA  
 Tel: 301-662-5019 Fax: 301-662-1731  
 Website [www.pmi-rf.com](http://www.pmi-rf.com), Email [sales@pmi-rf.com](mailto:sales@pmi-rf.com)



**SUMMARY TEST DATA**  
**ON SUCCESSIVE DETECTION LOG VIDEO AMPLIFIER (SDLVA)**

**CUSTOMER:** \_\_\_\_\_ **JOB NO:** \_\_\_\_\_  
**MODEL NO:** SDLVA-2020-70 **TESTED BY:** B. BAKER  
**OPTION NO:** 0518, A03, A07-50OHM **TEMPERATURE:** +25 °C  
**SERIAL NO:** \_\_\_\_\_ **DATE:** 6/4/2012

TEST ITEM NO:	PARAMETERS	SPECIFIED VALUE	MEASURED VALUE	REMARKS QA/QC
1	FREQUENCY RANGE	0.5GHz - 18GHz	Pass 0.5GHz - 18GHz	
2	FREQUENCY FLATNESS (0.5 - 18 GHz)	±2.0 dB (TYP)	Pass	
3	TSS (8 - 18 GHz)	-65 dBm (MIN)	Pass	
4	VSWR (0.5 - 18 GHz @-20 dBm)	3.0:1	Pass	
5	LOGGING RANGE	-65 dBm to +5 dBm	Pass	
6	LOG LINEARITY -65 dBm To +5 dBm	±1.75 dB (MAX)	Pass	
7	LOG SLOPE (±10% TOLERANCE)	20 mV/dB	Pass	
8	LOG TEMPERATURE STABILITY	±1.75 dB (0°C to 60°C)	Pass	
9	RISE TIME	20 ns (MAX)	Pass See Typical Characteristics	
10	RECOVERY TIME (MAX) (-65 dBm To +5 dBm)	200 ns (MAX)	Pass See Typical Characteristics	
11	OUTPUT POWER	+10 dBm ±2.5 dB (TYP)	Pass	
12	OUTPUT VIDEO LOAD	50 Ω ± 10% OR AS DESIRED	Pass	
13	POWER SUPPLY @ +12 V	600 mA (MAX)	Pass	
14	POWER SUPPLY @ -12 V	200 mA (MAX)	Pass	

QA / QC APPROVAL: \_\_\_\_\_

DATED: \_\_\_\_\_

## Return Loss

