



Planar Monolithics Industries, INC.

SUMMARY TEST DATA ON DIRECTIONAL DETECTOR

Customer
 Job No
 Model No : DD-20-23
 Serial No : PM112518

Tested By : Kevin Mason
 Temperature : +25°C
 Date : 12/13/01

TEST ITEM NO.	PARAMETERS	SPECIFIED VALUE	MEASURED VALUE			REMARKS QA/QC
			2.5 GHz (mV)	2.75 GHz (mV)	3.0 GHz (mV)	
1	Frequency	2.5-3.0 GHz	pass			
2	Insertion Loss	0.25dB max.	0.69 dB			
3	Insertion Loss Variation Over Freq.	0.2dB max.	0.28 dB			
4	VSWR	1.25:1 max.	Pass (see plot)			
5	Max. Input Power	3 Watts	pass			
6	Supply Voltage	±15VDC	ok			
7	Impedance	50 Ohms	50 Ohms			
8	Min. Directivity	20dB min.	pass			
9	Output Voltage Variation With Freq. and Temp.	±0.2dB max.	pass			
10	Detector Output Voltage: <u>Power In</u>	<u>Voltage Output</u>				
	+26dBm	150-220 mV	150.50	156.08	152.66	
	+23dBm	94-130 mV	95.51	99.90	94.16	
	+20dBm	58-83 mV	61.13	62.64	59.84	
	+16dBm	31-46mV	33.77	32.01	30.92	
11	Video BW	10 MHz min.	pass			

Production Manager Approval: _____ Date: _____

QA/QC Approval: _____ Date: _____

7311-G Grove Road Frederick, MD 21704 USA Phone: (301)631-1579 Fax: (301)662-2029
 email: planarsales@aol.com