

SUMMARY TEST DATA
ON
PVVAN-4080-60-MP

Customer: _____
 Job No: _____
 Model No: PVVAN-4080-60-MP
 Serial No: 13033
 Part No: _____

Tested By: G.Radtke
 Temperature: +25° C
 Date: Wednesday, March 17, 2021
 Drawing No: 27622595 Rev: A1

TEST ITEM NO.	PARAMETERS	SPECIFIED VALUE	TEST RESULTS	QA QC	
1	Frequency Range:	4.0 GHz to 8.0 GHz	4.0 GHz to 8.0 GHz	PMI QA 2	
2	Mean Attenuation Range:	60 dB	58.8 dB See Plot		
3	Insertion Loss:	2.5 dB Max.	2.2 dB See Plot		
4	VSWR:	2.0:1 Max	1.4:1 See Plot		
5	Power Rating:	+20 dBm (Operating) +30 dBm (Survival)	Pass		
6	Attenuation Flatness:	± 0.5 dB Typ. @ 10 dB ± 1.0 dB Typ. @ 20 dB ± 1.5 dB Typ. @ 40 dB ± 1.6 dB Typ. @ 60 dB	± 0.29 dB @ 10 dB ± 0.6 dB @ 20 dB ± 1.08 dB @ 40 dB ± 1.46 dB @ 60 dB See Plot		
7	Switching Time:	500 ns Max.	< 80 ns See Typical Characteristics		
8	Control:	10 dB / Volt Analog Controlled	Pass		
9	Power Supply:	+12 VDC @ 100 mA Typ. -12 VDC @ 50 mA Typ.	+12 VDC @ 28 mA -12 VDC @ 0 mA		PMI QA 2

Voltage Control (V)	Programmed Attenuation (dB)	Attenuation (dB)	Accuracy of Attenuation (dB)	Flatness (± dB)
1	10	10.28	0.28	0.29
2	20	20.08	0.08	0.60
3	30	29.95	-0.05	0.89
4	40	39.76	-0.24	1.08
5	50	49.56	-0.44	1.29
6	60	58.81	-1.19	1.46

QA/QC Approval:   **PMI QA 2** Date: 3/17/21

SUMMARY TEST DATA ON PVVAN-4080-60-MP

13033

