

**SUMMARY TEST DATA  
ON  
P2T-4G8G-70-T-SFF**

Customer: \_\_\_\_\_  
 SO No: \_\_\_\_\_  
 Model No: P2T-4G8G-70-T-SFF  
 Serial No: 13347  
 Part No: \_\_\_\_\_

Tested By: Tin M. L  
 Temperature: +25°C  
 Date: 11/15/2021  
 Drawing No: 27626442      Rev: A1

TEST ITEM NO	PARAMETERS	SPECIFIED VALUE	TEST RESULTS	QA QC
1	Frequency Range:	4.0 GHz to 8.0 GHz	4.0 GHz to 8.0 GHz	PMI QA 2
2	Insertion Loss:	1.9 dB Max.	1.69 dB See Plot	
3	Isolation:	70 dB Min.	92 dB See Plot	
4	VSWR: In/Out	1.6:1 Typ.	In 1.29:1 Out 1.35 :1 See Plot	
5	Switching Speed:	100 ns Max.	<100 ns See Typical Characteristics	
6	Input Power:	+30 dBm Max. (Survival) +20 dBm Max. (Operating)	Pass See Typical Characteristics	
7	DC Supply:	+5 VDC @ 100 mA Typ. -15 VDC @ 100 mA Typ.	+5 VDC @ 24 mA -15 VDC @ 59 mA	
8	Control Signal:	LOGIC TABLE CTL      FUNCTION 0      J1-J2 "Low Loss" 1      J1-J3 "Low Loss"	Pass	

QA/QC Approval: \_\_\_\_\_

PMI  
QA 2

Date: 11/17/2021

**SUMMARY TEST DATA**  
**ON**  
**P2T-4G8G-70-T-SFF**

13347

