



**SUMMARY TEST DATA  
ON  
DD-20-218-5PF-3-P-M**

Customer: \_\_\_\_\_ Tested By: Ken Schwartz  
SO No: \_\_\_\_\_ Temperature: +25°C  
Model No: DD-20-218-5PF-3-P-M Date: 12/16/2013  
Serial No: PL14398 Drawing No: 27620615 Rev: A1

TEST. ITEM NO	PARAMETERS	SPECIFIED VALUE	PASS FAIL	QA QC
1	Frequency Range:	2 TO 18 GHz	2 TO 18 GHz	SB
2	VSWR:	3.5: 1 MAX @-23 dBm	2.65:1 (See Plot #1)	SB
3	Frequency Flatness:	± 1.0 dB (Max)	± .55 dB	SB
4	Rise Time	5nS Typical	4.71 ns	SB
5	Voltage Sensitivity:	500 mV/mW	830 mV/mW	SB
6	Maximum Input Power:	+20 dBm	+20 dBm	SB

QA/QC Approval: *Stephen C. Byler* Date: 12/17/13



**SUMMARY TEST DATA  
ON  
DD-20-218-5PF-3-P-M**

**VSWR Plot**

CH2: B	--M	+2.658 SWR
10.00 /	REF	3.500 SWR

