



**SUMMARY TEST DATA
ON
DD-20-218-5PF-3-P-M**

Customer: _____ Tested By: Ken Schwartz
SO No: _____ Temperature: +25°C
Model No: DD-20-218-5PF-3-P-M Date: 12/16/2013
Serial No: PL14400 Drawing No: 27620615 Rev: A1

TEST. ITEM NO	PARAMETERS	SPECIFIED VALUE	PASS FAIL	QA QC
1	Frequency Range:	2 TO 18 GHz	2 TO 18 GHz	<i>SB</i>
2	VSWR:	3.5: 1 MAX @-23 dBm	3.31:1 (See Plot #1)	<i>SB</i>
3	Frequency Flatness:	± 1.0 dB (Max)	± .945 dB	<i>SB</i>
4	Rise Time	5nS Typical	4.73 ns	<i>SB</i>
5	Voltage Sensitivity:	500 mV/mW	570 mV/mW	<i>SB</i>
6	Maximum Input Power:	+20 dBm	+20 dBm	<i>SB</i>

QA/QC Approval: *Steve C. Byler* Date: 12/17/13



**SUMMARY TEST DATA
ON
DD-20-218-5PF-3-P-M**

VSWR Plot

CH2: B --M +3.314 SWR
10.00 / REF 3.500 SWR

