



**SUMMARY TEST DATA  
ON  
SDLVA-500M4G-CD-2**

PL15064

Customer: \_\_\_\_\_ Tested By: RCombs  
SO No: \_\_\_\_\_ Temperature: 25°C  
Model No: SDLVA-500M4G-CD-2 Date: 04/24/14  
Serial No: PL15064/1418 Drawing No: 27619941 Rev: B1

TEST. ITEM NO	PARAMETERS	SPECIFIED VALUE	PASS / FAIL	QA QC
1	Frequency Range:	500MHz to 4 GHz	See Plots #1A, 1B, 1C, 2	
2	RF Gain (Small Signal):	55dB Typ (J1 to J2)@-50dBm	55.3dB	
3	Video Flatness over Frequency:	± 50mV Max	See Plot #1A	
4	TSS:	-71dBm Max -73dBm Typ (25°C, -40C, +75°C)	-72dBm	
5	VSWR J1, J2,	2.0:1 Max	1.98:1 See Plot #2	
6	PSAT:	+13dBm Typ (J2)	+11.4dBm	
7	Power Input:	+17dBm CW Max (J1)	Pass	
8	Log Slope:	25mV/dB Typ(J3) (50Ω Load ) (25°C, -40C, +75°C)	See Plots #1A, 1B, 1C	
9	Log Range:	-70 to 0 dBm	See Plots #1A, 1B, 1C	
10	Log Linearity	±2.5dB (J3) (25°C, -40C, +75°C)	See Plots #1A, 1B, 1C	
11	DC Offset:	50 ± 50mV(J3)	73mV	
12	Pulse Range:	30ns to CW	30ns to CW	
13	Rise Time:	10ns Max (5ns Typ)	6.5ns	
14	Recovery Time:	60ns Max (40ns Typ)	33ns	
15	Harmonics:	15dBc Min -70 to 0dBm	16.8dBc	
16	DC Supply:	+15VDC @ 350 mA -15VDC @ 180 mA	+15VDC @ 204mA -15VDC @ 92mA	

QA/QC Approval: \_\_\_\_\_ Date: \_\_\_\_\_

7311-F Grove Road Frederick, MD 21704 USA Phone: (301)662-5019 Fax: (301)662-1731  
Email: [sales@pmi-rf.com](mailto:sales@pmi-rf.com)



**SUMMARY TEST DATA  
ON  
SDLVA-500M4G-CD-2**

PL15064

**VSWR PLOT #2**

