



**SUMMARY TEST DATA
ON
PTRAN-100M18G-SFB-3UVPX-MAH**

PL16313/1499

Customer: _____	Tested By: <u>RCombs</u>
SO No: _____	Temperature: <u>+25°C</u>
Model No: <u>PTRAN-100M18G-SFB-3UVPX-MAH</u>	Date: <u>7/12/19</u>
Serial No: <u>PL16313/1449</u>	Drawing No: <u>27622144</u> Rev: <u>A1</u>

J10 TX Output				
TEST ITEM NO:	PARAMETERS	SPECIFIED VALUE	MEASURED VALUE	REMARKS QA/QC
J1 – Receive Input				
1	Frequency	100MHz-18GHz	100MHz-18GHz	PMI QA1
2	Input Power Level	-80 dBm to -10 dBm	-80 dBm to -10 dBm	
J5 – IF Input				
3	Frequency	100MHz-4GHz	100MHz-4GHz	
4	Input Power Level	0 dBm Typical	0 dBm	
J7 LO1 Input				
5	Frequency	4GHz-20GHz	4GHz-20GHz	
6	Input Power Level	+15 dBm Typ.	+15 dBm	
J8 LO2 Input				
7	Input Frequency	4GHz-20GHz	4GHz-20GHz	
8	Input Power Level	+15 dBm Typ.	+15 dBm	
J4 IF Output				
9	Output Frequency	100MHz - 4GHz	100MHz - 4GHz	
10	Output Power Level	0dBm Typical for Limited SDLVA channels	-0dBm to +11dBm	PMI QA1



**SUMMARY TEST DATA
ON
PTRAN-100M18G-SFB-3UVPX-MAH**

PL16313/1499

11	Output Frequency	100MHz-18GHz	100MHz-18GHz	PMI QA1
12	Output Power Level	0 dBm to +10 dBm Typical with use of variable attenuator	+2.1dBm to +13dBm with use of variable attenuator	
Control Logic – LVDS				
13	LVDS 1	Receive 0 - Baseband Channel 1 - High Frequency Channel	0 - Baseband Channel 1 - High Frequency Channel	
14	LVDS 2	SDLVA2 0 - Limited Output 1 - Linear Output	0 - Limited Output 1 - Linear Output	
15	LVDS 3	SDLVA1 0 - Limited Output 1 - Linear Output	0 - Limited Output 1 - Linear Output	
16	LVDS 4	00000 - 0 dB Atten. 11111 - 31 dB Atten.	00000 - 0 dB Atten. 11111 - 31 dB Atten.	
17	LVDS 5	0 - Output to TX Filter Bank, RX- Backplane/Input (J1) 1 - Output to RX Filter Bank, RX- Transceiver Input	0 - Output to TX Filter Bank, RX- Backplane/Input (J1) 1 - Output to RX Filter Bank, RX- Transceiver Input	
18	LVDS 6	Receive Channel 000 - Thru Channel 001 - Channel 1 010 - Channel 2 011 - Channel 3 100 - Channel 4 101 - Channel 5 110 Not Defined 111 - Not Defined	000 - Thru Channel 001 - Channel 1 010 - Channel 2 011 - Channel 3 100 - Channel 4 101 - Channel 5 110 Not Defined 111 - Not Defined	
19	LVDS 7	Transmit 0 - Baseband Chan. 1 - High Freq. Chan.	0 - Baseband Chan. 1 - High Freq. Chan.	
20	LVDS 8	Transmit Channel 000 - Thru Channel 001 - Channel 1 010 - Channel 2 011 - Channel 3 100 - Channel 4 101 - Channel 5 110 Not Defined 111 - Not Defined	000 - Thru Channel 001 - Channel 1 010 - Channel 2 011 - Channel 3 100 - Channel 4 101 - Channel 5 110 Not Defined 111 - Not Defined	
21	LVDS X	00 M1-LO1 M2-LO1 01 M1-LO1 M2-LO2	00 M1-LO1 M2-LO1 01 M1-LO1 M2-LO2	PMI QA1



**SUMMARY TEST DATA
ON
PTRAN-100M18G-SFB-3UVPX-MAH**

PLI6313/1499

		10 M1-LO2 M2-LO1 11 M1-LO2 M2-LO2	10 M1-LO2 M2-LO1 11 M1-LO2 M2-LO2	PMI QA 1
22	Power Supply	+12V -12V +5V +3.3V	+12V @ 1.4A -12V @ 668mA +5V @ 753mA +3.3V @ 720mA	PMI QA 1

QA/QC Approval:  PMI QA 1 Date: 7/19/19