

DASH NO.	APPLICATION		REVISIONS			
	NEXT ASSY	USED ON	REV	DESCRIPTION	DATE	APPROVED
			1	RELEASE PER ECO 100791	1-9-07	JM
			2	REVISE PER ECO 101093	7-29-13	JM

REVISION	SHT NO.	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20
STATUS	LETTER	2	2																		

21	22	23	24	25	26	27	28	29	30	31	32	33	34	35	36	37	38	39	40	41	42	43	44	45

46	47	48	49	50	51	52	53	54	55	56	57	58	59	60	61	62	63	64	65	66	67	68	69	70

PMI CONFIDENTIAL & PROPRIETARY: The information contained herein is the property of PMI. Its use or reproductions is prohibited except as provided for by prior written authorization from PMI	PLANAR MONOLITHICS INDUSTRIES, INC. 4921 ROBERT J. MATHEWS PKWY, EL DORADO HILLS CA 95762 916-542-1401
	TEST DATA SHEET THRESHOLD DETECTOR GMTA-1003
CONTRACT NO.	
DRAWN: CAMERON N 1-09-07	
CHECKED	
PROJ ENGR JOHN M 1-09-07	
PROG MGR	
MFG. ENGR	
QA ENGR	
RELIABILITY:	
CUSTOMER	

	SIZE A	CAGE CODE 71A34	DWG. NO. ETD000030	REVISION 2
	SCALE			SHEET 1 OF 3

MODEL NO.: GMTA-1003

FREQUENCY: 8 – 18 GHz

SERIAL NO.: PL21508

PARAMETER	SPECIFICATION	MEASUREMENT
THRESHOLD LEVEL	Pin = -42 dBm @ 25 ° C	-40.3 dBm Average
RESPONSE TIME @ TTL " I " / TTL " O "	100 μs max	13 μs
INPUT VSWR	2.5 : 1 @ Pin = -10 dBm	2.16 : 1
DC POWER SUPPLY NO RF SIGNAL	+12V @ 200 mA	51 mA

THRESHOLD SETTING STABILITY
± 3 dB max OVER FREQUENCY @ TEMPERATURE


FREQ.	8 GHz	10 GHz	12 GHz	14 GHz	16 GHz	18 GHz
Pin @ 25 ° C	-41.2	-41.3	-39.6	-39.9	-39.9	-39.9
Pin @ 0 ° C	-41.4	-41.7	-39.9	-40.4	-40.2	-40.0
Pin @ 85 ° C	-40.8	-41.0	-39.0	-39.8	-39.6	-39.5

TESTED BY: Simon K.

DATE: 08/30/17

QA BY: [Signature]


DATE: 9-6-17

	SIZE A	CAGE CODE 71A34	DWG. NO. ETD000030	REVISION 2
	SCALE			SHEET 2 OF 3

INPUT VSWR @ -10 dBm

Model Number: GMTA-1003
Serial Number: PL21508

Temperature: +25C



SIZE
A

SCALE

CAGE CODE
71A34

DWG. NO.
ETD000030

REVISION 2

SHEET 3 OF 3