



**SUMMARY TEST DATA
ON
8CL1860-40-CD-SFF**

PL21793/1745

Customer: _____ Tested By: J. Wood
SO No: _____ Temperature: +25°C
Model No: 8CL1860-40-CD-SFF Date: 11/3/17
Serial No: PL21793/1745 Drawing No: 27609705 Rev: A1
Part No: _____



TEST ITEM NO.	PARAMETERS	SPECIFIED VALUE	MEASURED VALUE	QA/QC
1	Center Frequency:	1860 MHz Nom.	1860 MHz (See Plot)	PMI QA 2
2	3 dB Pass band Bandwidth:	40 MHz Min.	>40 MHz (See Plot)	
3	Pass band VSWR:	1.5:1 Max	1.338:1 (See Plot)	
4	Passband Insertion Loss:	7 dB Max	3.4 dB (See Plot)	
5	Loss Ripple (peak to peak):	0.5 dB Max	0.2 dB (See Plot)	
6	Rejection:	60 dB DC – 1800 MHz Min.	66.3 dB (See Plot)	
7	Rejection:	60 dB 1920 MHz–4000 MHz	69.2 dB (See Plot)	
8	Impedance (Source Load):	50 ohms Nom.	Pass	PMI QA 2

QA/QC Approval:  PMI QA 2 Date: 11/10/17



**SUMMARY TEST DATA
ON
8CL1860-40-CD-SFF**

PL21793/1745





**SUMMARY TEST DATA
ON
8CL1860-40-CD-SFF**

PL21793/1745

