



**SUMMARY TEST DATA  
ON  
4BP160-5-2A-PP**

Customer: \_\_\_\_\_ Tested By: A. Lopez  
SO No: \_\_\_\_\_ Temperature: +25°C  
Model No: 4BP160-5-2A-PP Date: 1/22/18  
Serial No: PL22037/1804 Drawing No: 27608446 Rev: A1

| TEST.<br>ITEM NO | PARAMETERS                    | SPECIFIED VALUE     | TEST<br>RESULTS                | QA<br>QC    |
|------------------|-------------------------------|---------------------|--------------------------------|-------------|
| 1                | Center<br>Frequency:          | 160 MHz $\pm$ 0.23% | 160.11 MHz                     | PMI<br>QA 2 |
| 2                | 3 dB Bandwidth:               | 5 MHz $\pm$ 5%      | 4.98 MHz<br>See plots          |             |
| 3                | Insertion Loss:<br>(Passband) | 10 dB Nominal       | 7.31dB<br>See Plot             |             |
| 4                | Rejection                     | 4 Section Response  | 4 Section Response<br>See Plot |             |
| 5                | VSWR in The Passband:         | 1.5:1 Max           | 1.22:1<br>See Plot             | PMI<br>QA 2 |

QA/QC Approval: \_\_\_\_\_

PMI  
QA 2

Date: \_\_\_\_\_

1/23/18



**SUMMARY TEST DATA  
ON  
4BP160-5-2A-PP**

**PL22037/1804**

