

SUMMARY TEST DATA
ON
PDC-800M2D5G-20C-NFF-60W

Customer: _____
SO No: _____
Model No: PDC-800M2D5G-20C-NFF-60W
Serial No: 23440
Part No: _____

Tested By: K. Mansfield
Temperature: +25°C
Date: 1/17/2022
Drawing No: 27625802 Rev: A1

TEST ITEM NO.	PARAMETERS	SPECIFIED VALUE	TEST RESULTS	QA QC
1	Frequency Range:	0.8 to 2.5 GHz	0.8 to 2.5 GHz	PMI QA 2
2	Insertion Loss:	≤ 0.4 dB (Excluding Coupled Power)	0.35 dB (See Plot)	PMI QA 2
3	VSWR:	$\leq 1.20:1$	1.08:1 (See Plot)	
4	Directivity:	20 dB Minimum	28 dB See Plot	
5	Coupling:	20 ± 1.0 dB	20 ± 0.49 dB See Plot	
6	Frequency Sensitivity:	$\leq \pm 0.7$ dB	+0.49 dB (See Plot)	
7	Power Handling:	Average ≤ 50 W Peak ≤ 1 kW	Average ≤ 50 W Peak ≤ 1 kW See Typical Characteristics	
8	Impedance:	50 Ω	50 Ω	PMI QA 2

QA/QC Approval: _____


PMI
QA 2

Date: 1/20/2022


**SUMMARY TEST DATA
ON
PDC-800M2D5G-20C-NFF-60W**

23440


Insertion Loss



VSWR



Directivity



Coupling

