



**SUMMARY TEST DATA  
ON  
P2T-2G18G-65-T-SFF**

Customer: \_\_\_\_\_  
 SO No: \_\_\_\_\_  
 Model No: P2T-2G18G-65-T-SFF  
 Serial No: PL23764/1844

Tested By: K. Mansfield  
 Temperature: +25°C  
 Date: 10/30/2018  
 Drawing No: 27635340      Rev: A1

TEST ITEM NO	PARAMETERS	SPECIFIED VALUE	TEST RESULTS	QA QC
1	Frequency Range:	2.0 GHz to 18.0 GHz	2.0 GHz to 18.0 GHz	
2	Insertion Loss:	3.0 dB Max.	2.49 dB See Plot	
3	Isolation:	65 dB Typ.	82 dB Typ. See Plot	
4	Input VSWR:	2.0:1 Max.	In 1.51:1 See Plot	
5	Switching Speed:	100 ns Max.	<50 ns See Typical Characteristics	
6	Impedance:	50 Ω	50 Ω	
7	Input Power:	+30 dBm Max. (Survival) +20 dBm (Operating)	Pass	
8	DC Supply:	+5 VDC @ 100 mA Typ. -15 VDC @ 100 mA Typ.	+5 VDC @ 24 mA -15 VDC @ 57 mA	
9	Control:	TTL "0" → (J1-J2) TTL "1" → (J1-J3)	Pass	

QA/QC Approval: \_\_\_\_\_

Date: \_\_\_\_\_



**SUMMARY TEST DATA  
ON  
P2T-2G18G-65-T-SFF**

PL23764/1844

